



# Specification Page

## ATV UTILITY UTILITY TRAILERS



	82" x 12' (3K)	82" x 14' (3K)	82" x 14' (7K)	82" x 16' (7K)
<b>Model</b>	H8212SHATV-030	H8214SHATV-030	H8214TSHATV-070	H8216TSHATV-070
<b>GAWR (lb./axle)</b>	3500	3500	3500	3500
<b>GVWR (lb.)</b>	2990	2990	7000	7000
<b>Curb Weight (lb.)</b>	1390	1410	1960	2050
<b>Payload Capacity (lb.)</b>	1600	1580	5040	4950
<b>Frame Construction</b>	4"x3" Angle	4"x3" Angle	4"x3" Angle	4"x3" Angle
<b>Crossmembers</b>	2"x2" Angle	2"x2" Angle	3"x2" Angle	3"x2" Angle
<b>Top Rail</b>	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
<b>Uprights/Sides</b>	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube
<b>Tongue Construction</b>	4" Channel	4" Channel	4" Channel	4" Channel
<b>Coupler</b>	2" A-Frame	2" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
<b>Coupler Height</b>	17 1/2"	17 1/2"	17 1/2"	17 1/2"
<b>Safety Chains</b>	Yes	Yes	Yes	Yes
<b>Jack</b>	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back
<b>Axle Type</b>	Leaf Spring Idler	Leaf Spring Idler	Leaf Spring Brake	Leaf Spring Brake
<b>Brakes</b>	-	-	4-Wheel Electric	4-Wheel Electric
<b>Breakaway Kit</b>	-	-	Yes	Yes
<b>Tires</b>	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
<b>Wheels</b>	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
<b>Trailer Plug</b>	4-Prong	4-Prong	7-Way	7-Way
<b>Exterior Lighting</b>	LED	LED	LED	LED
<b>Decking</b>	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
<b>Ramp Style</b>	Spring Assist Gate	Spring Assist Gate	Spring Assist Gate	Spring Assist Gate
<b>Ramp Length x Width</b>	50" x 77"	50" x 77"	50" x 77"	50" x 77"
<b>Load Capacity (lb.)</b>	2500	2500	2500	2500
<b>Overall Length</b>	16'-2"	18'-2"	18'-2"	20'-2"
<b>Overall Width</b>	102"	102"	102"	102"
<b>Overall Height</b>	70 1/4"	70 1/4"	70 1/4"	70 1/4"
<b>Deck Height</b>	20 1/4"	20 1/4"	20 1/4"	20 1/4"
<b>Deck Length</b>	12'-0"	14'-0"	14'-0"	16'-0"
<b>Deck Width</b>	82 1/4"	82 1/4"	82 1/4"	82 1/4"

### STANDARD FEATURES

Steel Angle Frame and Crossmembers 2" x 1-1/2" Steel Tube Uprights 2" x 2" Steel Tube Top Rail (2) 2" X 5' Side Ramp Conversions (3,075 lb. Load Rating) 4" Steel Channel Tongue 2K Rated Set-Back Jack with Foot	A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks 2x8 Treated, #1 Grade Wood Decking Welded Front Board Retainer and Rear End Cap 50" Spring Assisted Gate and Grab Handle Steel Tread Plate Fenders	Spring Suspension with Easy Lube Hubs Radial Tires on Black Steel Wheels Full LED, DOT Compliant Lighting Enclosed Sealed Wiring Harness Stake Pockets Spare Tire Mount
---	--	--