



# Specification Page

## ALUMINUM LOW SIDE FLATBED

UTILITY TRAILERS



	78" x 10' (3K)	78" x 12' (3K)	78" x 14' (3K)
<b>Model</b>	H7810LSA-030	H7812LSA-030	H7814LSA-030
<b>GAWR (lb./axle)</b>	3500	3500	3500
<b>GVWR (lb.)</b>	2990	2990	2990
<b>Curb Weight (lb.)</b>	720	770	820
<b>Payload Capacity (lb.)</b>	2270	2220	2170
<b>Frame Construction</b>	5" Extruded Tube	5" Extruded Tube	5" Extruded Tube
<b>Crossmembers</b>	None	None	None
<b>Top Rail</b>	None	None	None
<b>Uprights/Sides</b>	None	None	None
<b>Tongue Construction</b>	Straight Double Tube	Straight Double Tube	Straight Double Tube
<b>Coupler</b>	2" Straight	2" Straight	2" Straight
<b>Coupler Height</b>	18"	18"	18"
<b>Safety Chains</b>	Yes	Yes	Yes
<b>Jack</b>	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel
<b>Axle Type</b>	Torsion Idler	Torsion Idler	Torsion Idler
<b>Brakes</b>	-	-	-
<b>Breakaway Kit</b>	-	-	-
<b>Tires</b>	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
<b>Wheels</b>	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
<b>Trailer Plug</b>	4-Prong	4-Prong	4-Prong
<b>Exterior Lighting</b>	LED	LED	LED
<b>Decking</b>	Interlocking Aluminum Extrusion Plank	Interlocking Aluminum Extrusion Plank	Interlocking Aluminum Extrusion Plank
<b>Ramp Style</b>	Aluminum Bi-fold Gate	Aluminum Bi-fold Gate	Aluminum Bi-fold Gate
<b>Ramp Length x Width</b>	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 73"
<b>Load Capacity (lb.)</b>	2200	2200	2200
<b>Overall Length</b>	13'-8"	15'-6"	17'-4"
<b>Overall Width</b>	102"	102"	102"
<b>Overall Height</b>	45 1/2"	45 1/2"	45 1/2"
<b>Deck Height</b>	16 1/2"	16 1/2"	16 1/2"
<b>Deck Length</b>	10'-0"	12'-0"	14'-0"
<b>Deck Width</b>	78"	78"	78"

### STANDARD FEATURES

Aluminum Tube Extrusion Frame  
 Straight Double Tube Aluminum Tongue  
 2" A-Frame Posi-Lock Coupler  
 Dual Safety Chain and Hooks  
 1K Rated Swivel Jack with Caster Wheel

Interlocking Aluminum Extrusion Deck  
 16 1/2" Deck Height  
 54" Bi-fold Gate  
 Aluminum Radius Fenders with Backs

Torsion Idler Suspension with Easy Lube Hubs  
 Radial Tires on Aluminum Wheels  
 Sealed Wiring Harness  
 Full LED, DOT Compliant Lighting  
 Aluminum Stake Pockets