



ALUMINUM RAIL SIDE UTILITY - SINGLE AXLE

UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
Model	H6008RSA-030	H6010RSA-030	H6610RSA-030	H6612RSA-030	H7610RSA-030	H7612RSA-030	H8212RSA-030	H8214RSA-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	650	690	810	890	830	920	980	1050
Payload Capacity (lb.)	2340	2300	2180	2100	2160	2070	2010	1940
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube
Tongue Construction	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel
Axle Type	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
Ramp Style	Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate	
Ramp Length x Width	54 1/2" x 57"	54 1/2" x 57"	54 1/2" x 63"	54 1/2" x 63"	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 79"	54 1/2" x 79"
Load Capacity (lb.)	2200	2200	2200	2200	2200	2200	2200	2200
Overall Length	11'-10"	13'-10"	13'-9"	15'-9"	14'-4"	16'-4"	16'-9"	18'-9"
Overall Width	78 1/4"	78 1/4"	84 1/4"	84 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
Overall Height	49"	49"	49"	49"	49"	49"	49"	49"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	60 1/4"	60 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

Aluminum Angle Extrusion Frame
 Aluminum Angle Crossmembers
 2"x 1-1/2" Aluminum Extrusion Tube Uprights
 2" x 2" Aluminum Tube Top Rail
 4" Aluminum Tube Tongue
 A-Frame Posi-Lock Coupler

Dual Safety Chains and Hooks
 1K Rated Swivel Jack with Caster Wheel
 2x8 Treated, #1 Grade Wood Decking
 Front and Rear End Caps
 54" Bi-fold Gate
 Aluminum Fenders with Backs

Spring Suspension with Easy Lube Hubs
 Radial Tires on Aluminum Wheels
 Sealed Wiring Harness
 Full LED, DOT Compliant Lighting
 Aluminum Stake Pockets



Specification Page

ALUMINUM RAIL SIDE UTILITY - TANDEM AXLE

UTILITY TRAILERS



	82" x 14' (7K)	82" x 16' (7K)	82" x 18' (7K)	82" x 20' (7K)
Model	H8214TRSA-070	H8216TRSA-070	H8218TRSA-070	H8220TRSA-070
GAWR (lb./axle)	3500	3500	3500	3500
GVWR (lb.)	7000	7000	7000	7000
Curb Weight (lb.)	1485	1550	1640	1800
Payload Capacity (lb.)	5515	5450	5360	5200
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3" Channel	3" Channel	3" Channel	3" Channel
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube
Tongue Construction	5" Tube Wrapped with Tube Cross Brace			
Coupler	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains	Yes	Yes	Yes	Yes
Jack	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED
Decking	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
Ramp Style	Bi-fold Ramp Gate	Bi-fold Ramp Gate	Bi-fold Ramp Gate	Bi-fold Ramp Gate
Ramp Length x Width	54 1/2" x 79"	54 1/2" x 79"	54 1/2" x 79"	54 1/2" x 79"
Load Capacity (lb.)	2200	2200	2200	2200
Overall Length	18'-9"	20'-9"	22'-9"	24'-9"
Overall Width	102"	102"	102"	102"
Overall Height	49"	49"	49"	49"
Deck Height	18 1/2"	18 1/2"	18 1/2"	18 1/2"
Deck Length	14'-0"	16'-0"	18'-0"	20'-0"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

Aluminum Angle Extrusion Frame Aluminum Angle Crossmembers 2" x 1-1/2" Aluminum Extrusion Tube Uprights 2" x 2" Aluminum Tube Top Rail 5" Aluminum Tube Tongue A-Frame Posi-Lock Coupler	Dual Safety Chains and Hooks 2K Rated Set-Back Jack with Foot 2x8 Treated, #1 Grade Wood Decking Front and Rear End Caps 54" Bi-fold Gate Aluminum Teardrop Fenders with Backs	Spring Suspension with Easy Lube Hubs Radial Tires on Aluminum Wheels Sealed Wiring Harness Full LED, DOT Compliant Lighting Aluminum Stake Pockets
---	---	---