



ALUMINUM SOLID SIDE - SINGLE AXLE UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
Model	H6008SSA-030	H6010SSA-030	H6610SSA-030	H6612SSA-030	H7610SSA-030	H7612SSA-030	H8212SSA-030	H8214SSA-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	740	830	850	950	880	1010	1040	1130
Payload Capacity (lb.)	2250	2160	2140	2040	2110	1980	1950	1860
Frame Construction	Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP	
Crossmembers	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
Top Rail	None	None	None	None	None	None	None	None
Uprights/Sides	Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP	
Tongue Construction	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel
Axle Type	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
Ramp Style	Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate	
Ramp Length x Width	54 1/2" x 57"	54 1/2" x 57"	54 1/2" x 63"	54 1/2" x 63"	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 79"	54 1/2" x 79"
Load Capacity (lb.)	2200	2200	2200	2200	2200	2200	2200	2200
Overall Length	11'-10"	13'-10"	13'-9"	15'-9"	14'-4"	16'-4"	16'-9"	18'-9"
Overall Width	78 1/4"	78 1/4"	84 1/4"	84 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
Overall Height	49"	49"	49"	49"	49"	49"	49"	49"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	60 1/4"	60 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

<p>Formed 1/8" Polished Aluminum Diamond Plate Frame 3" Aluminum Channel Crossmembers Formed 1/8" Polished Aluminum Diamond Plate Sides 15" Tall Sides Aluminum Tube Tongue with Cross Brace A-Frame Posi-Lock Coupler</p>	<p>Dual Safety Chains and Hooks 1K Rated Swivel Jack with Caster Wheel 2x8 Treated, #1 Grade Wood Decking Front and Rear End Caps 54" Bi-fold Gate Aluminum Radius Fenders</p>	<p>Spring Suspension with Easy Lube Hubs Radial Tires on Aluminum Wheels Sealed Wiring Harness Full LED, DOT Compliant Lighting D-ring Tie Downs, Floor Mounted</p>
--	---	---