



Specification Page

ALUMINUM WOOD SIDE - SINGLE AXLE

UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
Model	H6008WSA-030	H6010WSA-030	H6610WSA-030	H6612WSA-030	H7610WSA-030	H7612WSA-030	H8212WSA-030	H8214WSA-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	940	980	1050	1110	1080	1150	1190	1280
Payload Capacity (lb.)	2050	2010	1940	1880	1910	1840	1800	1710
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x2" Tube 3 Board Treated Pine		2"x2" Tube 3 Board Treated Pine		2"x2" Tube 3 Board Treated Pine		2"x2" Tube 3 Board Treated Pine	
Tongue Construction	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	1K Rated Swivel		1K Rated Swivel		1K Rated Swivel		1K Rated Swivel	
Axle Type	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
Ramp Style	Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate	
Ramp Length x Width	54 1/2" x 57"	54 1/2" x 57"	54 1/2" x 63"	54 1/2" x 63"	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 79"	54 1/2" x 79"
Load Capacity (lb.)	2200	2200	2200	2200	2200	2200	2200	2200
Overall Length	11'-10"	13'-10"	13'-9"	15'-9"	14'-4"	16'-4"	16'-9"	18'-9"
Overall Width	78 1/4"	78 1/4"	84 1/4"	84 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
Overall Height	49"	49"	49"	49"	49"	49"	49"	49"
Deck Height	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	58"	58"	64"	64"	74"	74"	80"	80"

STANDARD FEATURES

Angle Aluminum Extrusion Frame
 Angle Aluminum Extrusion Crossmembers
 2"x2" Aluminum Extrusion Tube Uprights and Top Rail
 3 Treated Boards Sides- 24" Tall
 4" Aluminum Tube Tongue with Cross Brace
 A-Frame Posi-Lock Coupler

Dual Safety Chain and Hooks
 1K Rated Swivel Jack with Caster Wheel
 2x8 Treated, #1 Grade Wood Decking
 Front and Rear End Caps
 54" Bi-fold Gate
 Aluminum Radius Fenders

Spring Suspension with Easy Lube Hubs
 Radial Tires on Aluminum Wheels
 Sealed Wiring Harness
 Full LED, DOT Compliant Lighting
 (4) D-ring Tie Downs, Front and Side Mount