



# Specification Page

## FULL WIDTH INDUSTRIAL EQUIPMENT HAULER



	82"x16'+4' (14K)	82"x18'+4' (14K)	82"x20'+4' (14K)	82"x16'+4' (16K)	82"x18'+4' (16K)	82"x20'+4' (16K)
<b>Model</b>	H10216+4ILFW-140	H10218+4ILFW-140	H10220+4ILFW-140	H10216+4ILFW-160	H10218+4ILFW-160	H10220+4ILFW-160
<b>GAWR (lb./axle)</b>	7000	7000	7000	8000	8000	8000
<b>GVWR (lb.)</b>	14000	14000	14000	16000	16000	16000
<b>Curb Weight (lb.)</b>	3600	3760	3960	4045	4225	4400
<b>Payload Capacity (lb.)</b>	10400	10240	10040	11955	11775	11600
<b>Frame Construction</b>	6" Channel	6" Channel	6" Channel	8" Channel	8" Channel	8" Channel
<b>Crossmembers</b>	3" Channel, 16" OC			3" Channel, 16" OC		
<b>Tongue Construction</b>	6" Channel, Fully Wrapped			6" Channel, Fully Wrapped		
<b>Coupler</b>	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height
<b>Coupler Height</b>	11" - 22"	11" - 22"	11" - 22"	11" - 22"	11" - 22"	11" - 22"
<b>Safety Chains</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Jack</b>	12K Rated Drop Leg			12K Rated Drop Leg		
<b>Axle Type</b>	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
<b>Brakes</b>	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
<b>Breakaway Kit</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Tires</b>	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST215/75R17.5 'H'	ST215/75R17.5 'H'	ST215/75R17.5 'H'
<b>Wheels</b>	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5
<b>Trailer Plug</b>	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
<b>Exterior Lighting</b>	LED	LED	LED	LED	LED	LED
<b>Decking</b>	Pressure Treated Pine			Pressure Treated Pine		
<b>Dovetail</b>	4' Steel Self-Cleaning Dovetail			4' Steel Self-Cleaning Dovetail		
<b>Ramp Style</b>	Hinged, Double Spring Assisted			Hinged, Double Spring Assisted		
<b>Ramp Length x Width</b>	48" x 38"	48" x 38"	48" x 38"	48" x 38"	48" x 38"	48" x 38"
<b>Load Capacity (lb.)</b>	8500	8500	8500	8500	8500	8500
<b>Overall Length</b>	25'-10"	27'-10"	29'-10"	25'-10"	27'-10"	29'-10"
<b>Overall Width</b>	102"	102"	102"	102"	102"	102"
<b>Overall Height</b>	35"	35"	35"	35"	35"	35"
<b>Deck Height</b>	25 1/2"	25 1/2"	25 1/2"	28"	28"	28"
<b>Deck Length</b>	16'-2"	18'-2"	20'-2"	16'-2"	18'-2"	20'-2"
<b>Deck Width</b>	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"

### STANDARD FEATURES

<ul style="list-style-type: none"> <li>Steel Channel Frame</li> <li>3" Steel Channel Crossmembers</li> <li>6" Steel Channel Tongue</li> <li>HD Tube Bulkhead</li> <li>2 5/16" Adjustable Height Coupler</li> <li>Dual Safety Chains and Hooks</li> <li>12K Drop Leg Jack</li> </ul>	<ul style="list-style-type: none"> <li>2x8 Treated, #1 Grade Wood Decking</li> <li>Front and Rear Board Caps</li> <li>4' Steel Self Cleaning Dovetail</li> <li>Drop-Down Dock Leg Stands</li> <li>Full Width Bobcat Ramps with Double Spring Assist</li> <li>Tandem Formed Tread Plate Fenders</li> </ul>	<ul style="list-style-type: none"> <li>Spring Brake Suspension</li> <li>Radial Tires on Steel Wheels</li> <li>Sealed Wiring Harness</li> <li>Full LED, DOT Compliant Lighting</li> <li>Multiple Stake Pockets</li> <li>Spare Tire Mount</li> </ul>
---	---	--