



# Specification Page

## HH SERIES FLAT TOP CARGO - SINGLE AXLE ENCLOSED TRAILERS

	5' x 8' (3K)	5' x 10' (3K)	6' x 10' (3K)	6' x 12' (3K)	6' x 14' (3K)	7' x 10' (3K)	7' x 12' (3K)
<b>Model</b>	H608SFTV-035	H6010SFTV-035	H7210SFTV-035	H7212SFTV-035	H7214SFTV-035	H8410SFTV-035	H8412SFTV-035
<b>GAWR (lb./axle)</b>	3500	3500	3500	3500	3500	3500	3500
<b>GWVR (lb.)</b>	2990	2990	2990	2990	2990	2990	2990
<b>Curb Weight (lb.)</b>	1030	1100	1320	1375	1500	1530	1650
<b>Payload Capacity (lb.)</b>	1960	1890	1670	1615	1490	1460	1340
<b>Frame Construction</b>	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	4" Tube Steel	4" Tube Steel
<b>Crossmembers</b>	Formed Channel Steel, 24" OC		Formed Channel Steel, 24" OC			Formed Channel Steel, 24" OC	
<b>Wall Uprights</b>	Tube Steel, 24" OC		Tube Steel, 24" OC			Tube Steel, 24" OC	
<b>Roof Bows</b>	Galvanized Tube Steel, 24" OC		Galvanized Tube Steel, 24" OC			Galvanized Tube Steel, 24" OC	
<b>Exterior Sheeting</b>	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
<b>Tongue Construction</b>	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	4" Tube Steel	4" Tube Steel
<b>Coupler</b>	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
<b>Coupler Height</b>	17"	17"	17"	17"	17"	17"	17"
<b>Safety Chains</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Jack</b>	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
<b>Axle Type</b>	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler
<b>Brakes</b>	-	-	-	-	-	-	-
<b>Breakaway Kit</b>	-	-	-	-	-	-	-
<b>Tires</b>	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
<b>Wheels</b>	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
<b>Trailer Plug</b>	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat
<b>Exterior Lighting</b>	LED	LED	LED	LED	LED	LED	LED
<b>Interior Lighting</b>	(1) 12V, LED Dome Light		(1) 12V, LED Dome Light			(1) 12V, LED Dome Light	
<b>Side Escape Door</b>	N/A	Yes	Yes	Yes	Yes	Yes	Yes
<b>Side Door (H x W)</b>	-	64" x 32"	68" x 32"	68" x 32"	68" x 32"	68" x 32"	68" x 32"
<b>Rear Door Type</b>	Spring Assist Ramp		Spring Assist Ramp			Spring Assist Ramp	
<b>Rear Opening (H x W)</b>	65" x 58"	65" x 58"	70" x 66"	70" x 66"	70" x 66"	70" x 78"	70" x 78"
<b>Load Capacity (lb.)</b>	1000	1000	1000	1000	1000	1000	1000
<b>Overall Length</b>	13'-6"	15'-6"	15'-6"	17'-6"	19'-6"	15'-6"	17'-6"
<b>Overall Width</b>	93"	93"	93"	93"	93"	102"	102"
<b>Overall Height</b>	7'-2"	7'-2"	7'-8"	7'-8"	7'-8"	8'-0"	8'-0"
<b>Overall Interior Length</b>	12'-2"	14'-2"	14'-2"	16'-2"	12'-2"	14'-2"	14'-2"
<b>Deck Box Length</b>	57"	57"	69"	69"	81"	81"	81"
<b>Interior Width</b>	-	-	-	-	-	-	-
<b>Between Wheel Wells</b>	66"	66"	73"	73"	73"	73"	73"
<b>Interior Height</b>	18"	18"	18"	18"	18"	18"	18"
<b>Deck Height</b>	9'-10"	11'-10"	11'-10"	13'-10"	9'-10"	11'-10"	13'-10"

### STANDARD FEATURES

<ul style="list-style-type: none"> <li>Steel Tube Frame</li> <li>Steel Formed Channel Crossmembers</li> <li>Steel Tube Wall Uprights</li> <li>Galvanized Steel Tube Row Bows</li> <li>Body Fully Undercoated</li> <li>Vapor Barrier</li> <li>Flat Roof with .024 Aluminum Sheeting</li> <li>30" V-Nose</li> <li>Steel Tube A-Frame Tongue</li> <li>2" A-Frame Posi-Lock Coupler</li> <li>Dual Safety Chains and Hooks</li> </ul>	<ul style="list-style-type: none"> <li>2K Rated Swivel Jack</li> <li>.030 Aluminum Exterior Sheeting</li> <li>Standard Color Options: White / Black / Charcoal / Silver</li> <li>24" Aluminum Tread Plate Rock Guard</li> <li>Weather Coated Tongue and Rear Bulkhead</li> <li>3/8" Engineered Wood Interior Walls</li> <li>Aluminum H-Channel Wall Transitions</li> <li>66" Wall Height - 5' Wide Models</li> <li>72" Wall Height - 6' and 7' Wide Models</li> </ul>	<ul style="list-style-type: none"> <li>3/4" Engineered Wood Flooring</li> <li>32" Side Door RV-Style Latch (Excludes 5x8)</li> <li>Aluminum Door Hold Back</li> <li>Spring Assist Rear Ramp Door</li> <li>Aluminum Tapered Square Fenders</li> <li>Drop Spring Idler Suspension with Easy Lube Hubs</li> <li>Radial Tires on White Steel Wheels</li> <li>12V LED Dome Light and Switch, Wall Mounted</li> <li>Full LED, DOT Compliant Lighting</li> </ul>
--	---	---



## HH SERIES FLAT TOP CARGO - TANDEM AXLE

6' AND 7' WIDE ENCLOSED TRAILERS

	6' x 12'	7' x 12'	7' x 14'	7' x 16'	7' x 18'	7' x 20'
<b>7K Model</b>	H7212TFTV-070	H8412TFTV-070	H8414TFTV-070	H8416TFTV-070	H8418TFTV-070	H8420TFTV-070
<b>GAWR (lb./axle)</b>	3500	3500	3500	3500	3500	3500
<b>GWVR (lb.)</b>	7000	7000	7000	7000	7000	7000
<b>Curb Weight (lb.)</b>	1750	1930	2100	2220	2380	2470
<b>Payload Capacity (lb.)</b>	5250	5070	4900	4780	4620	4530
<b>10K Model</b>	H7212TFTV-100	H8412TFTV-100	H8414TFTV-100	H8416TFTV-100	H8418TFTV-100	H8420TFTV-100
<b>GAWR (lb./axle)</b>	na	5200	5200	5200	5200	5200
<b>GWVR (lb.)</b>	na	9900	9900	9900	9900	9900
<b>Curb Weight (lb.)</b>	na	2200	2250	2400	2630	2870
<b>Payload Capacity (lb.)</b>	na	7700	7650	7500	7270	7030
<b>Frame Construction</b>	4" Tube Steel	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
<b>Crossmembers</b>	Formed Channel Steel, 16" OC					
<b>Wall Uprights</b>	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC
<b>Roof Bows</b>	Galvanized Tube Steel, 24" OC					
<b>Exterior Sheeting</b>	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
<b>Tongue Construction</b>	4" Tube Steel	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
<b>Coupler</b>	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
<b>Coupler Height</b>	18"	18"	18"	18"	18"	18"
<b>Safety Chains</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Jack</b>	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
<b>Axle Type</b>	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake
<b>Brakes</b>	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
<b>Breakaway Kit</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Tires: 7K</b>	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
<b>10K</b>	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
<b>Wheels: 7K</b>	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
<b>10K</b>	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
<b>Trailer Plug</b>	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
<b>Exterior Lighting</b>	LED	LED	LED	LED	LED	LED
<b>Interior Lighting</b>	(2) 12V, LED Dome Light					
<b>Side Escape Door</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Side Door (H x W)</b>	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"
<b>Rear Door Type</b>	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
<b>Rear Opening (H x W)</b>	69" x 66"	69" x 78"	69" x 78"	69" x 78"	69" x 78"	69" x 78"
<b>Load Capacity (lb.)</b>	1000	1000	1000	1000	1000	1000
<b>Overall Length</b>	17'-6"	17'-10"	19'-10"	21'-10"	23'-10"	26'-10"
<b>Overall Width</b>	92"	102"	102"	102"	102"	102"
<b>Overall Height: 7K</b>	7'-9"	8'-1"	8'-1"	8'-1"	8'-3"	8'-3"
<b>10K</b>	-	8'-2"	8'-2"	8'-2"	8'-4"	8'-4"
<b>Interior Length</b>	14'-2"	14'-2"	16'-2"	18'-2"	20'-2"	22'-3"
<b>Deck Box Length</b>	11'-10"	11'-10"	13'-10"	15'-10"	17'-10"	19'-10"
<b>Interior Width</b>	69"	82"	82"	82"	82"	82"
<b>Between Wheel Wells</b>	-	-	-	-	-	-
<b>Interior Height</b>	73"	73"	73"	73"	73"	73"
<b>Deck Height: 7K</b>	19"	19"	19"	19"	20"	20"
<b>10K</b>	20"	20"	20"	20"	20"	20"

### STANDARD FEATURES

<ul style="list-style-type: none"> <li>Steel Tube Frame</li> <li>Steel Formed Channel Crossmembers</li> <li>Steel Tube Wall Uprights</li> <li>Galvanized Steel Tube Row Bows</li> <li>Body Fully Undercoated</li> <li>Vapor Barrier</li> <li>Flat Roof with .024 Aluminum Sheeting</li> <li>30" V-Nose</li> <li>Steel Tube A-Frame Tongue</li> <li>2 5/16" A-Frame Posi-Lock Coupler</li> </ul>	<ul style="list-style-type: none"> <li>Dual Safety Chains and Hooks</li> <li>2K Rated Swivel Jack</li> <li>.030 Aluminum Exterior Sheeting</li> <li>Standard Color Options:               <ul style="list-style-type: none"> <li>White / Black / Charcoal / Silver</li> </ul> </li> <li>24" Aluminum Tread Plate Rock Guard</li> <li>Weather Coated Tongue and Rear Bulkhead</li> <li>3/8" Engineered Wood Interior Walls - 72" Height</li> <li>Aluminum H-Channel Wall Transitions</li> <li>3/4" Engineered Wood Flooring</li> </ul>	<ul style="list-style-type: none"> <li>36" Side Door RV-Style Latch</li> <li>Aluminum Door Hold Back</li> <li>Spring Assist Rear Ramp Door</li> <li>Aluminum Teardrop Fenders</li> <li>Drop Spring Brake Suspension</li> <li>Easy Lube Hubs</li> <li>Radial Tires on White Steel Wheels</li> <li>(2) 12V LED Dome Light and Switch, Wall Mounted</li> <li>Full LED, DOT Compliant Lighting</li> </ul>
---	---	---



## HH SERIES FLAT TOP CARGO - TANDEM AXLE

8' AND 101" WIDE ENCLOSED TRAILERS

	8' x 16'	8' x 18'	8' x 20'	101" x 16'	101" x 18'	101" x 20'
7K Model	H9616TFTV-070	H9618TFTV-070	H9620TFTV-070	H10116TFTV-070	H10118TFTV-070	H10120TFTV-070
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500
GWVR (lb.)	7000	7000	7000	7000	7000	7000
Curb Weight (lb.)	2500	2650	2760	2610	2810	3010
Payload Capacity (lb.)	4500	4350	4240	4390	4190	3990
10K Model	H9616TFTV-100	H9618TFTV-100	H9620TFTV-100	H10116TFTV-100	H10118TFTV-100	H10120TFTV-100
GAWR (lb./axle)	5200	5200	5200	5200	5200	5200
GWVR (lb.)	9900	9900	9900	9900	9900	9900
Curb Weight (lb.)	2725	2950	3100	2850	3200	3330
Payload Capacity (lb.)	7175	6950	6800	7050	6700	6570
Frame Construction	4" Tube Steel	6" Tube Steel	6" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Formed Channel Steel, 16" OC			Formed Channel Steel, 16" OC		
Wall Uprights	Tube Steel, 24" OC			Tube Steel, 24" OC		
Roof Bows	Galvanized Tube Steel, 24" OC			Galvanized Tube Steel, 24" OC		
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Coupler	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
Coupler Height	18"	18"	18"	18"	18"	18"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Coupler Mount			2K Rated Coupler Mount		
Axle Type	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes
Tires: 7K	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels: 7K	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light					
Side Escape Door	Yes	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	68" x 90"	68" x 90"	68" x 90"	68" x 95"	68" x 95"	68" x 95"
Load Capacity (lb.)	4000	4000	4000	4000	4000	4000
Overall Length	21'-10"	23'-10"	26'-10"	21'-10"	23'-10"	26'-10"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height: 7K	8'-1"	8'-3"	8'-3"	8'-1"	8'-3"	8'-3"
10K	8'-2"	8'-4"	8'-4"	8'-2"	8'-4"	8'-4"
Overall Interior Length	18'-2"	20'-2"	22'-3"	18'-2"	20'-2"	22'-3"
Deck Box Length	15'-10"	17'-10"	19'-10"	15'-10"	17'-10"	19'-10"
Interior Width	93"	93"	93"	98-1/2"	98-1/2"	98-1/2"
Between Wheel Wells	82"	82"	82"	82"	82"	82"
Interior Height	73"	73"	73"	73"	73"	73"
Deck Height: 7K	19"	20"	20"	19"	20"	20"
10K	20"	21"	21"	20"	21"	21"

### STANDARD FEATURES

<ul style="list-style-type: none"> <li>Steel Tube Frame</li> <li>Steel Formed Channel Crossmembers</li> <li>Steel Tube Wall Uprights</li> <li>Galvanized Steel Tube Row Bows</li> <li>Body Fully Undercoated</li> <li>Vapor Barrier</li> <li>Flat Roof with .024 Aluminum Sheeting</li> <li>30" V-Nose</li> <li>Steel Tube A-Frame Tongue</li> <li>2 5/16" A-Frame Posi-Lock Coupler</li> </ul>	<ul style="list-style-type: none"> <li>Dual Safety Chains and Hooks</li> <li>2K Rated Coupler Mount Jack</li> <li>.030 Aluminum Exterior Sheeting</li> <li>Standard Color Options:               <ul style="list-style-type: none"> <li>White / Black / Charcoal / Silver</li> </ul> </li> <li>24" Aluminum Tread Plate Rock Guard</li> <li>Weather Coated Tongue and Rear Bulkhead</li> <li>3/8" Engineered Wood Interior Walls - 72" Height</li> <li>Aluminum H-Channel Wall Transitions</li> <li>3/4" Engineered Wood Flooring</li> </ul>	<ul style="list-style-type: none"> <li>36" Side Door RV-Style Latch</li> <li>Aluminum Door Hold Back</li> <li>Spring Assist Rear Ramp Door</li> <li>Aluminum Teardrop Fenders</li> <li>Drop Spring Brake Suspension</li> <li>Easy Lube Hubs</li> <li>Radial Tires on White Steel Wheels</li> <li>(2) 12V LED Dome Light and Switch, Wall Mounted</li> <li>Full LED, DOT Compliant Lighting</li> </ul>
---	--	---