



HH SERIES ROUND TOP CARGO - SINGLE AXLE

ENCLOSED TRAILERS

	6' x 10' (3K)	6' x 12' (3K)	6' x 14' (3K)	7' x 10' (3K)	7' x 12' (3K)
Model	H7210SRT-035	H7212SRT-035	H7214SRT-035	H8410SRT-035	H8412SRT-035
GAWR (lb./axle)	3500	3500	3500	3500	3500
GWVR (lb.)	2990	2990	2990	2990	2990
Curb Weight (lb.)	1250	1350	1450	1400	1500
Payload Capacity (lb.)	1740	1640	1540	1590	1490
Frame Construction	3" Tube Steel	3" Tube Steel	3" Tube Steel	4" Tube Steel	4" Tube Steel
Crossmembers	Formed Channel Steel, 24" OC			Formed Channel Steel, 24" OC	
Wall Uprights	Tube Steel, 24" OC			Tube Steel, 24" OC	
Roof Bows	Galvanized Tube Steel, 24" OC			Galvanized Tube Steel, 24" OC	
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	3" Tube Steel	3" Tube Steel	3" Tube Steel	4" Tube Steel	4" Tube Steel
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	18 3/4"	18 3/4"	18 3/4"	17 1/4"	17 1/4"
Safety Chains	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
Axle Type	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler
Brakes	-	-	-	-	-
Breakaway Kit	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat
Exterior Lighting	LED	LED	LED	LED	LED
Interior Lighting	12V, LED Dome Light	12V, LED Dome Light	12V, LED Dome Light	12V, LED Dome Light	12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	62" x 32"	62" x 32"	62" x 32"	62" x 32"	62" x 32"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	68" x 66"	68" x 66"	68" x 66"	68" x 78"	68" x 78"
Load Capacity (lb.)	1000	1000	1000	1000	1000
Overall Length	14' 3"	16'-1"	17'-10"	14'-0"	16'-1"
Overall Width	93"	93"	93"	102"	102"
Overall Height	7'-11"	7'-11"	7'-11"	7'-11"	7'-11"
Overall Interior Length	10'-8"	12'-9"	14'-9"	10'-9"	12'-9"
Deck Box Length	9'-10"	11'-10"	13'-10"	9'-10"	11'-10"
Interior Width	69"	69"	69"	81 1/2"	81 1/2"
Between Wheel Wells	-	-	-	-	-
Interior Height	76"	76"	76"	76"	76"
Deck Height	19 1/2"	19 1/2"	19 1/2"	18"	18"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Tube Frame Steel Formed Channel Crossmembers Steel Tube Wall Uprights Galvanized Steel Tube Row Bows Body Fully Undercoated Vapor Barrier Round Roof with .030 Aluminum Sheeting Custom Fiberglass Nose Cap White on White Black on Color Steel Tube A-Frame Tongue 	<ul style="list-style-type: none"> 2" A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks 2K Rated Swivel Jack .030 Aluminum Exterior Sheeting Standard Color Options: <ul style="list-style-type: none"> White / Black / Charcoal / Silver 24" Aluminum Tread Plate Rock Guard Weather Coated Tongue and Rear Bulkhead 3/8" Engineered Wood Interior Walls Aluminum H-Channel Wall Transitions 	<ul style="list-style-type: none"> 66" Wall Height 3/4" Engineered Wood Flooring 32" Side Door RV-Style Latch Aluminum Door Hold Back Spring Assist Rear Ramp Door Aluminum Tapered Square Fenders Drop Spring Idler Suspension with Easy Lube Hubs Radial Tires on White Steel Wheels 12V LED Dome Light and Switch, Wall Mounted Full LED, DOT Compliant Lighting
--	---	---



HH SERIES ROUND TOP CARGO - TANDEM AXLE

7' WIDE ENCLOSED TRAILERS

	7' x 12'	7' x 14'	7' x 16'	7' x 18'	7' x 20'
7K Model	H8412TRT-070	H8414TRT-070	H8416TRT-070	H8418TRT-070	H8420TRT-070
GAWR (lb./axle)	3500	3500	3500	3500	3500
GWVR (lb.)	7000	7000	7000	7000	7000
Curb Weight (lb.)	1850	2050	2165	2425	2570
Payload Capacity (lb.)	5150	4950	4835	4575	4430
10K Model	H8412TRT-100	H8414TRT-100	H8416TRT-100	H8418TRT-100	H8420TRT-100
GAWR (lb./axle)	5200	5200	5200	5200	5200
GWVR (lb.)	9900	9900	9900	9900	9900
Curb Weight (lb.)	2100	2280	2400	2695	2770
Payload Capacity (lb.)	7800	7620	7500	7205	7130
Frame Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Formed Channel Steel, 16" OC				
Wall Uprights	Tube Steel 24", OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC
Roof Bows	Galvanized Steel Tube 24" OC				
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Coupler	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
Coupler Height	18"	18"	18"	18"	18"
Safety Chains	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
Axle Type	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes
Tires: 7K	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels: 7K	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	74 1/2" x 78"	74 1/2" x 78"	74 1/2" x 78"	74 1/2" x 78"	74 1/2" x 78"
Load Capacity (lb.)	1000	1000	1000	1000	1000
Overall Length	16'-2"	18'-2"	20'-2"	22'-2"	24'-2"
Overall Width	102"	102"	102"	102"	102"
Overall Height: 7K	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"
10K	8'-7"	8'-7"	8'-7"	8'-7"	8'-7"
Overall Interior Length	12'-9"	14'-9"	16'-9"	18'-9"	20'-9"
Deck Box Length	11'-10"	13'-10"	15'-10"	17'-10"	19'-10"
Interior Width	81"	81"	81"	81"	81"
Between Wheel Wells	-	-	-	-	-
Interior Height	82"	82"	82"	82"	82"
Deck Height: 7K	18"	18"	18"	20"	20"
10K	19"	19"	19"	21"	21"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Tube Frame Steel Formed Channel Crossmembers Steel Tube Wall Uprights Galvanized Steel Tube Row Bows Body Fully Undercoated and Vapor Barrier Round Roof with .030 Aluminum Sheeting Custom Fiberglass Nose Cap <ul style="list-style-type: none"> White on White Black on Color Steel Tube A-Frame Tongue 2 5/16" A-Frame Posi-Lock Coupler 	<ul style="list-style-type: none"> Dual Safety Chains and Hooks 2K Rated Swivel Jack .030 Aluminum Exterior Sheeting Standard Color Options: <ul style="list-style-type: none"> White / Black / Charcoal / Silver 24" Aluminum Tread Plate Rock Guard Weather Coated Tongue and Rear Bulkhead 3/8" Engineered Wood Interior Walls - 72" Height Aluminum H-Channel Wall Transitions 3/4" Engineered Wood Flooring 	<ul style="list-style-type: none"> 36" Side Door RV-Style Latch Aluminum Door Hold Back Spring Assist Rear Ramp Door Aluminum Teardrop Fenders Drop Spring Brake Suspension Easy Lube Hubs Radial Tires on White Steel Wheels (2) 12V LED Dome Light and Switch, Wall Mounted Full LED, DOT Compliant Lighting
--	---	---



Specification Page

HH SERIES ROUND TOP CARGO - TANDEM AXLE

8' & 101" WIDE ENCLOSED TRAILERS

	8' x 16'	8' x 18'	8' x 20'	101" x 16'	101" x 18'	101" x 20'
7K Model	H9616TRT-070	H9618TRT-070	H9620TRT-070	H10116TRT-070	H10118TRT-070	H10120TRT-070
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500
GWVR (lb.)	7000	7000	7000	7000	7000	7000
Curb Weight (lb.)	2350	2670	2800	2600	2750	2830
Payload Capacity (lb.)	4650	4330	4200	4400	4250	4170
10K Model	H9616TRT-100	H9618TRT-100	H9620TRT-100	H10116TRT-100	H10118TRT-100	H10120TRT-100
GAWR (lb./axle)	5200	5200	5200	5200	5200	5200
GWVR (lb.)	9900	9900	9900	9900	9900	9900
Curb Weight (lb.)	2550	2850	3110	2910	3150	3200
Payload Capacity (lb.)	7350	7050	6790	6990	6750	6700
Frame Construction	4" Tube Steel	6" Tube Steel	6" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Formed Channel Steel, 16" OC			Formed Channel Steel, 16" OC		
Wall Uprights	Tube Steel 24" OC			Tube Steel 24" OC		
Roof Bows	Galvanized Tube Steel 24" OC			Galvanized Tube Steel 24" OC		
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	4" Tube Steel	6" Tube Steel	6" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Coupler	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
Coupler Height	18"	18"	18"	18"	18"	18"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Coupler Mount			2K Rated Coupler Mount		
Axle Type	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes
Tires: 7K	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels: 7K	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light			(2) 12V, LED Dome Light		
Side Escape Door	Yes	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	74 1/2" x 90"	74 1/2" x 90"	74 1/2" x 90"	74 1/2" x 90"	74 1/2" x 90"	74 1/2" x 90"
Load Capacity (lb.)	4000	4000	4000	4000	4000	4000
Overall Length	20'-6"	22'-6"	24'-6"	20'-6"	22'-6"	24'-6"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height: 7K	8'-8"	8'-8"	8'-8"	8'-8"	8'-8"	8'-8"
10K	8'-9"	8'-9"	8'-9"	8'-9"	8'-9"	8'-9"
Overall Interior Length	16'-9"	18'-9"	20'-9"	16'-9"	18'-9"	20'-9"
Deck Box Length	15'-10"	17'-10"	19'-10"	15'-10"	17'-10"	19'-10"
Interior Width	93"	93"	93"	98 1/2"	98 1/2"	98 1/2"
Between Wheel Wells	82"	82"	82"	82"	82"	82"
Interior Height	82"	82"	82"	82"	82"	82"
Deck Height: 7K	22"	22"	22"	22"	22"	22"
10K	23"	23"	23"	23"	23"	23"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Tube Frame Steel Formed Channel Crossmembers Steel Tube Wall Uprights Galvanized Steel Tube Row Bows Body Fully Undercoated and Vapor Barrier Round Roof with .030 Aluminum Sheeting Custom Fiberglass Nose Cap White on White Black on Color Steel Tube A-Frame Tongue 2 5/16" A-Frame Posi-Lock Coupler 	<ul style="list-style-type: none"> Dual Safety Chains and Hooks 2K Rated Coupler Mount Jack .030 Aluminum Exterior Sheeting Standard Color Options: <ul style="list-style-type: none"> White / Black / Charcoal / Silver 24" Aluminum Tread Plate Rock Guard Weather Coated Tongue and Rear Bulkhead 3/8" Engineered Wood Interior Walls - 72" Height Aluminum H-Channel Wall Transitions 3/4" Engineered Wood Flooring 	<ul style="list-style-type: none"> 36" Side Door RV-Style Latch Aluminum Door Hold Back Spring Assist Rear Ramp Door Aluminum Teardrop Fenders Drop Spring Brake Suspension Easy Lube Hubs Radial Tires on White Steel Wheels (2) 12V LED Dome Light and Switch, Wall Mounted Full LED, DOT Compliant Lighting
--	--	---