



Specification Page

HEAVY DUTY RAIL SIDE LANDSCAPE

UTILITY TRAILERS



	82" x 16' (10K)	82" x 18' (10K)	82" x 20' (10K)
Model	H8216HTRS-100	H8218HTRS-100	H8220HTRS-100
GAWR (lb./axle)	5200	5200	5200
GVWR (lb.)	9900	9900	9900
Curb Weight (lb.)	2210	2280	2400
Payload Capacity (lb.)	7690	7620	7500
Frame Construction	5"x3" Angle	5"x3" Angle	5"x3" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	3"x2" Tube	3"x2" Tube	3"x2" Tube
Uprights/Sides	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube
Tongue Construction	5" Channel	5" Channel	5" Channel
Coupler	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"
Safety Chains	Yes	Yes	Yes
Jack	7K Rated Set-Back	7K Rated Set-Back	7K Rated Set-Back
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes
Tires	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED
Decking	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
Ramp Style	HD Reinforced Ladder Style, Spring Assist Gate		
Ramp Length x Width	50" x 77"	50" x 77"	50" x 77"
Load Capacity (lb.)	2800	2800	2800
Overall Length	20'-2"	22'-2"	24'-2"
Overall Width	102"	102"	102"
Overall Height	69"	69"	69"
Deck Height	20"	20"	20"
Deck Length	16'-0"	18'-0"	20'-0"
Deck Width	82 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

Steel Angle Frame	Dual Safety Chains and Hooks	Spring Suspension with Easy Lube Hubs
Steel Angle Crossmembers	7K Drop Leg Jack, Set-Back	Radial Tires on Black Steel Wheels
2" x 1-1/2" Steel Tube Uprights	2x8 Treated, #1 Grade Wood Decking	Full LED, DOT Compliant Lighting
3" x 2" Steel Tube Top Rail	Welded Front Board Retainer and Rear End Cap	Enclosed Sealed Wiring Harness
5" Steel Channel Tongue	50" Ladder Style, Spring Assist Gate and Grab Handle	Stake Pockets
2 5/16" A-Frame Posi-Lock Coupler	Steel Formed Tread Plate Fenders	Spare Tire Mount