

Specification Page

HOMEOWNER DUMP

DUMP TRAILERS





	62" x 8' (5K)	62" x 10' (7K)	
Model	H6208UD-15-052	H6210UD-15-070	
GAWR (lb./axle)	5200	3500	
GVWR (lb.)	5000	7000	
Curb Weight (lb.)	1400	1890	
Payload Capacity (lb.)	3600	5110	
Frame Construction	4" Channel	4" Channel	
Crossmembers	3" Channel	3" Channel	
Sides	15" Tall, 12-Gauge Steel	15" Tall, 12-Gauge Steel	
Tongue Construction	4" Channel	4" Channel	
Coupler	2 5/16" A-frame	2 5/16" A-frame	
Coupler Height	17 1/2"	17 1/2"	
Safety Chains	Yes	Yes	
Jack	2K Rated Coupler Mount	2K Rated Coupler Mount	
Axle Type	Leaf Spring Brake	Leaf Spring Brake	
Brakes	Electric	4-Wheel Electric	
Breakaway Kit	Yes	Yes	
Tires	ST225/75R15 'D'	ST205/75R15 'C'	
Wheels	15", 6 on 5.5	15", 5 on 4.5	
Trailer Plug	6 on 5.5	5 on 4.5	
Exterior Lighting	7-Way	7-Way	
Decking	LED	LED	
Gate Style	12-Gauge Steel	12-Gauge Steel	
Ramp Style	Barn Door Gate	Barn Door Gate	
Ramp Length x Width	-	-	
Load Capacity (lb.)	-	-	
Overall Length	-	-	
Overall Width	12'-6"	14'-6"	
Overall Height	86 1/4"	86 1/4"	
Bed Height	45 1/2"	45 1/2"	
Bed Length	24"	24"	
Bed Width	8'	10'	

STANDARD FEATURES

4" Steel Tube Frame	2" A-Frame Ball Coupler	(4) D-Ring Tie-Downs
3" Steel Channel Crossmembers	Dual Safety Chains and Hooks	2-Way Corded Remote
12" Tall Sides	2K Swivel Jack with Caster	Protected Remote Holder
Integrated Side Body Stiffening System	One Piece 11-Gauge Smooth Steel Bed	Power Up, Power Down Single Stroke Ram Cylinder
Front and Rear Panels Serve as Ramps	Spring Idler Suspension with Easy Lube Hub	12V Hydraulic Pump (3000 PSI)
Ramps Include Anti-Skid Finish	Radial Tires on 10" Wheels	Deep Cycle Battery
Detachable 4" Steel Tube Tongue	Full LED, DOT Compliant Lighting	