



# Specification Page

## POWER TILT DECKOVER

DECKOVER TRAILERS



	102" X 22' (15K)	102" X 22' (17.6K)
<b>Model</b>	H10222PTHD-B-150	H10222PTHD-B-176
<b>GAWR (lb./axle)</b>	7000	8000
<b>GVWR (lb.)</b>	15000	17600
<b>Curb Weight (lb.)</b>	4485	4825
<b>Payload Capacity (lb.)</b>	10515	12775
<b>Frame Construction</b>	10", 12 lb./ft I-Beam	10", 12 lb./ft I-Beam
<b>Crossmembers</b>	3" Channel	3" Channel
<b>Tongue Construction</b>	6" Channel	6" Channel
<b>Coupler</b>	2 5/16" Adj. Height	2 5/16" Adj. Height
<b>Coupler Height</b>	19"-27"	19"-27"
<b>Safety Chains</b>	Yes	Yes
<b>Jack</b>	12K Rated Drop Leg	12K Rated Drop Leg
<b>Axle Type</b>	Slipper Spring Brake	Slipper Spring Brake
<b>Brakes</b>	4-Wheel Electric	4-Wheel Electric
<b>Breakaway Kit</b>	Yes	Yes
<b>Tires</b>	ST235/80R16 'E'	ST215/75R17.5 'H'
<b>Wheels</b>	16", 8 on 6.5	17.5", 8 on 6.5
<b>Trailer Plug</b>	7-Way	7-Way
<b>Exterior Lighting</b>	LED	LED
<b>Decking</b>	Pressure Treated Pine	Pressure Treated Pine
<b>Dovetail</b>	Reverse Taper Cut	Reverse Taper Cut
<b>Ramp Style</b>	None	None
<b>Ramp Length x Width</b>	-	-
<b>Load Capacity (lb.)</b>	-	-
<b>Overall Length</b>	27'-6"	27'-6"
<b>Overall Width</b>	102"	102"
<b>Overall Height</b>	41"	41"
<b>Deck Height</b>	34"	34"
<b>Deck Length</b>	22'-2"	22'-2"
<b>Deck Width</b>	97 1/4"	97 1/4"
<b>Load Angle</b>	15 Deg.	15 Deg.

### STANDARD FEATURES

Low Profile 10", 12 lb. Steel I-Beam Frame 3" Steel Channel Crossmembers HD Tube Bulkhead 6" Steel Channel Tongue Integrated Side Steps 2 5/16" Adjustable Height Coupler Dual Safety Chains and Hooks 12K Drop Leg Jack	2x8 Treated, #1 Grade Wood Decking Front and Rear Board Caps Reverse Taper Cut Dovetail Dual Ram Hydraulic Jack 12V Hydraulic Pump (3000 PSI) Tongue Mounted Pump Box 2-Button Remote and Battery	Spring Brake Suspension Radial Tires on Black Steel Wheels Sealed Wiring Harness Full LED, DOT Compliant Lighting (4) Welded D-Ring Tie Downs Multiple Stake Pockets with Rub Rails (3/8" on 17.6K Models) Spare Tire Mount
---	---	--