



Specification Page

RAIL SIDE UTILITY SINGLE AXLE

UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
Model	H6008RS-030	H6010RS-030	H6610RS-030	H6612RS-030	H7610RS-030	H7612RS-030	H8212RS-030	H8214RS-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	750	810	890	990	970	1050	1110	1210
Payload Capacity (lb.)	2240	2180	2100	2000	2020	1940	1880	1780
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube
Tongue Construction	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Set-Back		2K Rated Set-Back		2K Rated Set-Back		2K Rated Set-Back	
Axle Type	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
Ramp Style	Spring Assist Ramp Gate		Spring Assist Ramp Gate		Spring Assist Ramp Gate		Spring Assist Ramp Gate	
Ramp Length x Width	50" x 55"	50" x 55"	50" x 61"	50" x 61"	50" x 71"	50" x 71"	50" x 77"	50" x 77"
Load Capacity (lb.)	2500	2500	2500	2500	2500	2500	2500	2500
Overall Length	12'-2"	14'-2"	14'-2"	16'-2"	14'-2"	16'-2"	16'-2"	18'-2"
Overall Width	80 1/2"	80 1/2"	86 1/2"	86 1/2"	94 1/2"	94 1/2"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	8'-2"	10'-2"	10'-2"	12'-2"	10'-2"	12'-2"	12'-2"	14'-2"
Deck Width	60 1/4"	60 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Angle Frame and Crossmembers 2" x 1-1/2" Steel Tube Uprights 2" x 2" Steel Tube Top Rail 4" Steel Channel Tongue A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks 	<ul style="list-style-type: none"> 2K Rated Set-Back Jack with Foot 2x8 Treated, #1 Grade Wood Decking Welded Front Board Retainer and Rear End Cap 50" Spring Assisted Gate and Grab Handle Steel Tread Plate Fenders Spring Suspension with Easy Lube Hubs 	<ul style="list-style-type: none"> Radial Tires on Black Steel Wheels Enclosed Sealed Wiring Harness Full LED, DOT Compliant Lighting Stake Pockets Spare Tire Mount
--	--	---



RAIL SIDE UTILITY TANDEM AXLE

UTILITY TRAILERS



	82" x 14' (7K)	82" x 16' (7K)	82" x 18' (7K)	82" x 20' (7K)
Model	H8214TRS-070	H7216TRS-070	H8218TRS-070	H8220TRS-070
GAWR (lb./axle)	3500	3500	3500	3500
GVWR (lb.)	7000	7000	7000	7000
Curb Weight (lb.)	1610	1790	1890	1970
Payload Capacity (lb.)	5390	5210	5110	5030
Frame Construction	4"x3" Angle	4"x3" Angle	4"x3" Angle	4"x3" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube
Tongue Construction	4" Channel	4" Channel	4" Channel	4" Channel
Coupler	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains	Yes	Yes	Yes	Yes
Jack	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED
Decking	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
Ramp Style	Spring Assist Ramp Gate	Spring Assist Ramp Gate	Spring Assist Ramp Gate	Spring Assist Ramp Gate
Ramp Length x Width	50" x 77"	50" x 77"	50" x 77"	50" x 77"
Load Capacity (lb.)	2500	2500	2500	2500
Overall Length	18'-2"	20'-2"	22'-2"	24'-2"
Overall Width	102"	102"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	14'-2"	16'-2"	18'-2"	20'-2"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Angle Frame and Crossmembers 2" x 1-1/2" Steel Tube Uprights 2" x 2" Steel Tube Top Rail 4" Steel Channel Tongue A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks 	<ul style="list-style-type: none"> 2K Rated Set-Back Jack with Foot 2x8 Treated, #1 Grade Wood Decking Welded Front Board Retainer and Rear End Cap 50" Spring Assisted Gate and Grab Handle Steel Tread Plate Fenders Spring Suspension with Easy Lube Hubs 	<ul style="list-style-type: none"> Radial Tires on Black Steel Wheels Enclosed Sealed Wiring Harness Full LED, DOT Compliant Lighting Stake Pockets Spare Tire Mount
--	--	---