



Specification Page

SPEED LOADER[®] TILT CAR HAULER



	MXA - Manual Tilt				EXA - Electric Tilt			
	82" x 18' (7K)	82" x 20' (7K)	82" x 22' (7K)	82" x 24' (7K)	82" x 18' (7K)	82" x 20' (7K)	82" x 22' (7K)	82" x 24' (7K)
Model	H8218MX-070	H8220MX-070	H8222MX-070	H8224MX-070	H8218EX-070	H8220EX-070	H8222EX-070	H8224EX-070
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	7000	7000	7000	7000	7000	7000	7000	7000
Curb Weight (lb.)	1900	2010	2210	2450	1960	2190	2390	2580
Payload Capacity (lb.)	5100	4990	4790	4550	5040	4810	4610	4420
Frame Construction	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel
Crossmembers	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
Tongue Construction	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel
Coupler	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
Coupler Height	16 3/4"	16 3/4"	16 3/4"	16 3/4"	16 3/4"	16 3/4"	16 3/4"	16 3/4"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	7K Rated Drop Leg, Set-Back				7K Rated Drop Leg, Set-Back			
Axle Type	Leaf Spring Brake				Leaf Spring Brake			
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine				Pressure Treated Pine			
Dovetail	Reverse Taper Cut Dovetail				Reverse Taper Cut Dovetail			
Ramp Style	-	-	-	-	-	-	-	-
Ramp Length x Width	-	-	-	-	-	-	-	-
Load Capacity (lb.)	-	-	-	-	-	-	-	-
Overall Length	23'-10"	25'-10"	27'-10"	29'-10"	23'-10"	25'-10"	27'-10"	29'-10"
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"
Overall Height	32"	32"	32"	32"	32"	32"	32"	32"
Deck Height	23"	23"	23"	23"	23"	23"	23"	23"
Deck Length	18'-2"	20'-2"	22'-2"	24'-2"	18'-2"	20'-2"	22'-2"	24'-2"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"
Load Angle	14 Deg.	12 Deg.	10 Deg.	8 Deg.	14 Deg.	12 Deg.	10 Deg.	8 Deg.

STANDARD FEATURES

5" Steel Channel Frame
3" Steel Channel Crossmembers
HD Bulkhead
5" Steel Channel Tongue
2 5/16" A-Frame Posi-Lock Coupler
Dual Safety Chain and Hooks

7K Drop Leg Jack, Set-Back
2x8 Treated, #1 Grade Wood Decking
Front and Rear Board Caps
Reverse Taper Cut Dovetail
Tandem Formed Tread Plate Fenders
Spring Brake Suspension with Easy Lube Hubs

Radial Tires on Black Steel Wheels
Sealed Wiring Harness
Full LED, DOT Compliant Lighting
Multiple Stake Pockets
Spare Tire Mount