



# Specification Page

## STANDARD DUTY DOVETAIL

DECKOVER TRAILERS



	102"x14'+4"	102"x16'+4"	102"x18'+4"	102"x20'+4"	102"x22'+4"	102"x24'+4"
10K Model	H10214+4HDL-100	H10216+4HDL-100	H10218+4HDL-100	H10220+4HDL-100	H10222+4HDL-100	H10224+4HDL-100
GAWR (lb./axle)	5200	5200	5200	5200	5200	5200
GVWR (lb.)	9900	9900	9900	9900	9900	9900
Curb Weight (lb.)	3100	3300	3500	3700	4000	4200
Payload Capacity (lb.)	6800	6600	6400	6200	5900	5700
14K Model	H10214+4HDL-140	H10216+4HDL-140	H10218+4HDL-140	H10220+4HDL-140	H10222+4HDL-140	H10224+4HDL-140
SKU #	4H5H25	4H6H25	4H7H75	4H9H50	5H1H50	5H3H50
GAWR (lb./axle)	7000	7000	7000	7000	7000	7000
GVWR (lb.)	14000	14000	14000	14000	14000	14000
Curb Weight (lb.)	3350	3550	3750	3950	4250	4450
Payload Capacity (lb.)	10650	10450	10250	10050	9750	9550
Frame Construction	10" I-Beam	10" I-Beam	10" I-Beam	10" I-Beam	10" I-Beam	10" I-Beam
Crossmembers	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC
Sides	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel
Tongue Construction	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel
Coupler	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height
Coupler Height	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes
Tires: 10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
14K	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'
Wheels: 10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
14K	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine			Pressure Treated Pine		
Dovetail	4' Self Cleaning			4' Self Cleaning		
Ramp Style	Hinged, Spring Assisted			Hinged, Spring Assisted		
Ramp Length x Width	66" x 21"	66" x 21"	66" x 21"	66" x 21"	66" x 21"	66" x 21"
Load Capacity (lb.)	6200	6200	6200	6200	6200	6200
Overall Length	25'-0"	27'-0"	29'-0"	31'-0"	33'-0"	35'-0"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height: 10K	37"	37"	37"	37"	37"	37"
14K	38"	38"	38"	38"	38"	38"
Deck Height: 10K	30"	30"	30"	30"	30"	30"
14K	31"	31"	31"	31"	31"	31"
Deck Length	14'-0"	16'-0"	18'-0"	20'-0"	22'-0"	24'-0"
Deck Width	97 1/4"	97 1/4"	97 1/4"	97 1/4"	97 1/4"	97 1/4"

### STANDARD FEATURES

<ul style="list-style-type: none"> <li>10" I-Beam Frame</li> <li>5" Steel Channel Sides</li> <li>3" Steel Channel Crossmembers</li> <li>HD Tube Bulkhead</li> <li>6" Steel Channel Tongue</li> <li>Integrated Steps</li> </ul>	<ul style="list-style-type: none"> <li>2 5/16" Adjustable Height Coupler</li> <li>Dual Safety Chains and Hooks</li> <li>7K Rated Drop Leg Jack, Set-Back</li> <li>2x8 Treated, #1 Grade Wood Decking</li> <li>Front and Rear Board Caps</li> <li>Spring Brake Suspension with Easy Lube Hubs</li> </ul>	<ul style="list-style-type: none"> <li>Radial Tires on Black Steel Wheels</li> <li>Mud Flaps</li> <li>Sealed Wiring Harness</li> <li>Full LED, DOT Compliant Lighting</li> <li>Multiple Stake Pockets with Rub Rails</li> <li>Spare Tire Mount</li> </ul>
--	---	---



# Specification Page

## STANDARD DUTY

### DECKOVER TRAILERS



	102" x 14'	102" x 16'	102" x 18'	102" x 20'	102" x 22'	102" x 24'
10K Model	H10214HDL-100	H10216HDL-100	H10218HDL-100	H10220HDL-100	H10222HDL-100	H10224HDL-100
GAWR (lb./axle)	5200	5200	5200	5200	5200	5200
GVWR (lb.)	9900	9900	9900	9900	9900	9900
Curb Weight (lb.)	2550	2750	2950	3150	3450	3650
Payload Capacity (lb.)	7350	7150	6950	6750	6450	6250
14K Model	H10214HDL-140	H10216HDL-140	H10218HDL-140	H10220HDL-140	H10222HDL-140	H10224HDL-140
SKU #	3H9H00	4H0H00	4H1H00	4H2H00	4H4H00	4H6H00
GAWR (lb./axle)	7000	7000	7000	7000	7000	7000
GVWR (lb.)	14000	14000	14000	14000	14000	14000
Curb Weight (lb.)	2800	3000	3200	3400	3750	3950
Payload Capacity (lb.)	11200	11000	10800	10600	10250	10050
Frame Construction	10" I-Beam	10" I-Beam	10" I-Beam	10" I-Beam	10" I-Beam	10" I-Beam
Crossmembers	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC	3" Channel, 16" OC
Sides	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel	5" Channel
Tongue Construction	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel
Coupler	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height
Coupler Height	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes
Tires: 10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
14K	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'
Wheels: 10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
14K	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
Dovetail	-	-	-	-	-	-
Ramp Style	Optional	Optional	Optional	Optional	Optional	Optional
Ramp Length x Width	-	-	-	-	-	-
Load Capacity (lb.)	-	-	-	-	-	-
Overall Length	19'-3"	21'-3"	23'-3"	25'-3"	27'-3"	29'-3"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height: 10K	37"	37"	37"	37"	37"	37"
14K	38"	38"	38"	38"	38"	38"
Deck Height: 10K	30"	30"	30"	30"	30"	30"
14K	31"	31"	31"	31"	31"	31"
Deck Length	14'-2"	16'-2"	18'-2"	20'-2"	20'-2"	20'-2"
Deck Width	97 1/4"	97 1/4"	97 1/4"	97 1/4"	97 1/4"	97 1/4"

### STANDARD FEATURES

10" I-Beam Frame  
5" Steel Channel Sides  
3" Steel Channel Crossmembers  
HD Tube Bulkhead  
6" Steel Channel Tongue  
Integrated Steps

2 5/16" Adjustable Height Coupler  
Dual Safety Chains and Hooks  
7K Rated Drop Leg Jack, Set-Back  
2x8 Treated, #1 Grade Wood Decking  
Front and Rear Board Caps  
Spring Brake Suspension with Easy Lube Hubs

Radial Tires on Black Steel Wheels  
Mud Flaps  
Sealed Wiring Harness  
Full LED, DOT Compliant Lighting  
Multiple Stake Pockets with Rub Rails  
Spare Tire Mount