



Specification Page

SUPER DELUXE RAMP INDUSTRIAL EQUIPMENT HAULER



	82"x16'+4' (14K)	82"x18'+4' (14K)	82"x20'+4' (14K)	82"x16'+4' (16K)	82"x18'+4' (16K)	82"x20'+4' (16K)
Model	H8216+4ILSDR-140	H8218+4ILSDR-140	H8220+4ILSDR-140	H8216+4ILSDR-160	H8218+4ILSDR-160	H8220+4ILSDR-160
GAWR (lb./axle)	7000	7000	7000	8000	8000	8000
GVWR (lb.)	14000	14000	14000	16000	16000	16000
Curb Weight (lb.)	3360	3600	3740	3865	4045	4220
Payload Capacity (lb.)	10640	10400	10260	12135	11955	11780
Frame Construction	6" Channel	6" Channel	6" Channel	8" Channel	8" Channel	8" Channel
Crossmembers	3" Channel, 16" OC			3" Channel, 16" OC		
Tongue Construction	6" Channel, Fully Wrapped			6" Channel, Fully Wrapped		
Coupler	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height	2 5/16" Adj. Height
Coupler Height	11" - 22"	11" - 22"	11" - 22"	11" - 22"	11" - 22"	11" - 22"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	12K Rated Drop Leg			12K Rated Drop Leg		
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes
Tires	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST215/75R17.5 'H'	ST215/75R17.5 'H'	ST215/75R17.5 'H'
Wheels	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine			Pressure Treated Pine		
Dovetail	4' Steel Self-Cleaning Dovetail			4' Steel Self-Cleaning Dovetail		
Ramp Style	Hinged Full Width, Double Spring Assisted			Hinged Full Width, Double Spring Assisted		
Ramp Length x Width	48" x 38"	48" x 38"	48" x 38"	48" x 38"	48" x 38"	48" x 38"
Load Capacity (lb.)	8500	8500	8500	8500	8500	8500
Overall Length	25'-10"	27'-10"	29'-10"	25'-10"	27'-10"	29'-10"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height	35"	35"	35"	35"	35"	35"
Deck Height	25 1/2"	25 1/2"	25 1/2"	28"	28"	28"
Deck Length	16'-2"	18'-2"	20'-2"	16'-2"	18'-2"	20'-2"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Channel Frame 3" Steel Channel Crossmembers 6" Steel Channel Tongue HD Tube Bulkhead 2 5/16" Adjustable Height Coupler Dual Safety Chains and Hooks 12K Drop Leg Jack 	<ul style="list-style-type: none"> 2x8 Treated, #1 Grade Wood Decking Front and Rear Board Caps 4' Steel Self Cleaning Dovetail Drop-Down Dock Leg Stands Full Width Bobcat Ramps with Double Spring Assist Tandem Formed Tread Plate Fenders 	<ul style="list-style-type: none"> Spring Brake Suspension Radial Tires on Steel Wheels Sealed Wiring Harness Full LED, DOT Compliant Lighting Multiple Stake Pockets Spare Tire Mount
---	---	--