



Specification Page

TANDEM AXLE GRAVITY TILT EQUIPMENT HAULER



	82" x 16'	82" x 18'	82" x 20'	82" x 16'+4'	82" x 16'+6'	82" x 18'+4'	82" x 18'+6'	82" x 20'+4'	82" x 20'+6'
14K Model	H16GTL-140	H18GTL-140	H20GTL-140	H16+4GTL-140	H16+6GTL-140	H18+4GTL-140	H18+6GTL-140	H20+4GTL-140	H20+6GTL-140
GAWR (lb./axle)	7000	7000	7000	7000	7000	7000	7000	7000	7000
GVWR (lb.)	14000	14000	14000	14000	14000	14000	14000	14000	14000
Curb Weight (lb.)	3460	3400	3740	3200	3310	3310	3540	3540	3700
Payload Capacity (lb.)	10540	10600	10260	10800	10690	10690	10460	10460	10300
16K Model	H16GTL-160	H18GTL-160	H20GTL-160	H16+4GTL-160	H16+6GTL-160	H18+4GTL-160	H18+6GTL-160	H20+4GTL-160	H20+6GTL-160
SKU #	6H1H50	6H2H50	6H3H50	6H3H50	6H4H50	6H4H50	6H5H50	6H6H00	6H7H50
GAWR (lb./axle)	8000	8000	8000	8000	8000	8000	8000	8000	8000
GVWR (lb.)	16000	16000	16000	16000	16000	16000	16000	16000	16000
Curb Weight (lb.)	3960	3900	4240	3710	3910	3910	4100	4100	4900
Payload Capacity (lb.)	12040	12100	11760	12290	12090	12090	11900	11900	11100
Frame Construction: 14K	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel
16K	8" Channel	8" Channel	8" Channel	8" Channel	8" Channel	8" Channel	8" Channel	8" Channel	8" Channel
Crossmembers	3" Channel, 16" OC					3" Channel, 16" OC			
Tongue Construction	6" Channel, Wrapped					6" Channel, Wrapped			
Coupler	2 5/16" Adj. Height					2 5/16" Adj. Height			
Coupler Height	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"	11"-19"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	12K Rated Drop Leg					12K Rated Drop Leg			
Axle Type	Drop Spring Brake					Drop Spring Brake			
Brakes	4-Wheel Electric					4-Wheel Electric			
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tires: 14K	ST235/80R16 'E'					ST235/80R16 'E'			
16K	ST215/75R17.5 'H'					ST215/75R17.5 'H'			
Wheels: 14K	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5
16K	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine					Pressure Treated Pine			
Dovetail	Reverse Taper Cut Dovetail					Reverse Taper Cut Dovetail			
Overall Length	24'-5"	26'-5"	28'-5"	24'-5"	26'-5"	26'-5"	28'-5"	28'-5"	30'-5"
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"	102"
Overall Height: 14K	32"	32"	32"	32"	32"	32"	32"	32"	32"
16K	34"	34"	34"	34"	34"	34"	34"	34"	34"
Deck Height: 14K	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"
16K	21"	21"	21"	21"	21"	21"	21"	21"	21"
Deck Length	16'-2"	18'-2"	20'-2"	20'-4"	22'-4"	22'-4"	24'-4"	24'-4"	26'-4"
Stationary Deck Width	80"	80"	80"	80"	80"	80"	80"	80"	80"
Tilting Deck Width	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"
Between Fender Width	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"
Load Angle	11 Deg.	10 Deg.	9 Deg.	11 Deg.	11 Deg.	10 Deg.	10 Deg.	9 Deg.	9 Deg.

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Channel Frame 3" Steel Channel Crossmembers HD Tube Bulkhead 6" Steel Channel Tongue 2 5/16" Adjustable Height Coupler Dual Safety Chain and Hooks 12K Drop Leg Jack 	<ul style="list-style-type: none"> 2x8 Treated, #1 Grade Wood Decking Front and Rear Board Caps Reverse Taper Cut Dovetail Tandem Formed Tread Plate Fenders Drop Spring Brake Suspension Radial Tires on Steel Wheels Sealed Wiring Harness 	<ul style="list-style-type: none"> Full LED, DOT Compliant Lighting Multiple Stake Pockets Spare Tire Mount Hydraulic Cushion Load Cylinder Cylinder Shut-off Valve Heavy Duty Hinge Latches
--	---	--