



Specification Page

TOPLINE[®] SERIES CARGO

7' WIDE ENCLOSED TRAILERS

	7' x 12'	7' x 14'	7' x 16'	7' x 18'	7' x 20'
7K Model	H8412TT-070	H8414TT-070	H8416TT-070	H8418TT-070	H8420TT-070
GAWR (lb./axle)	3500	3500	3500	3500	3500
GWVR (lb.)	7000	7000	7000	7000	7000
Curb Weight (lb.)	2300	2415	2530	2810	3100
Payload Capacity (lb.)	4700	4585	4470	4190	3900
10K Model	H8412TT-100	H8414TT-100	H8416TT-100	H8418TT-100	H8420TT-100
GAWR (lb./axle)	5200	5200	5200	5200	5200
GWVR (lb.)	9900	9900	9900	9900	9900
Curb Weight (lb.)	2585	2700	2800	3110	3400
Payload Capacity (lb.)	7315	7200	7100	6790	6500
Frame Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC
Wall Uprights	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC
Roof Bows	Galvanized Tube Steel, 16" OC				
Exterior Sheeting	.040 Aluminum	.040 Aluminum	.040 Aluminum	.040 Aluminum	.040 Aluminum
Tongue Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Coupler	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
Coupler Height	17"	17"	17"	18"	18"
Safety Chains	Yes	Yes	Yes	Yes	Yes
Jack	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back
Axle Type	Torsion Brake	Torsion Brake	Torsion Brake	Torsion Brake	Torsion Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes
Tires: 7K	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels: 7K	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	74 1/2" x 78"	74 1/2" x 78"	74 1/2" x 78"	74 1/2" x 78"	74 1/2" x 78"
Load Capacity (lb.)	4000	4000	4000	4000	4000
Overall Length	16'-7"	18'-7"	20'-7"	22'-7"	24'-7"
Overall Width	102"	102"	102"	102"	102"
Overall Height: 7K	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"
10K	8'-7"	8'-7"	8'-7"	8'-7"	8'-7"
Overall Interior Length	12'-9"	14'-9"	16'-9"	18'-9"	20'-9"
Deck Box Length	11'-10"	13'-10"	15'-10"	17'-10"	19'-10"
Interior Width	81"	81"	81"	81"	81"
Between Wheel Wells	-	-	-	-	-
Interior Height	82"	82"	82"	82"	82"
Deck Height: 7K	18"	18"	18"	20"	20"
10K	19"	19"	19"	21"	21"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Tube Frame Steel Tube Crossmembers Steel Tube Wall Uprights Galvanized Steel Tube Row Bows Body Fully Undercoated and Vapor Barrier Round Roof with .030 Aluminum Sheeting Custom Fiberglass Nose Cap <ul style="list-style-type: none"> White on White Black on Color Steel Tube A-Frame Tongue 2 5/16" A-Frame Posi-Lock Coupler 	<ul style="list-style-type: none"> Dual Safety Chains and Hooks 7K Rated Drop Leg Jack .040 Aluminum Exterior Sheeting Standard Color Options: <ul style="list-style-type: none"> White / Black 24" Aluminum Tread Plate Rock Guard Weather Coated Tongue and Rear Bulkhead 3/8" Engineered Wood Interior Walls - 72" Height Aluminum H-Channel Wall Transitions 3/4" Engineered Wood Flooring 	<ul style="list-style-type: none"> 36" Side Door RV-Style Latch Aluminum Door Hold Back Spring Assist Rear Ramp Door Ramp Transition Flap and Spring Cover Aluminum Teardrop Fenders Torsion Brake Suspension with Easy Lube Hubs Radial Tires on Aluminum Wheels (2) 12V LED Dome Light and Switch, Wall Mounted Full LED, DOT Compliant Lighting (1) Posi-Vent
--	---	--



TOPLINE[®] SERIES CARGO

8' & 101" WIDE ENCLOSED TRAILERS

	8' x 16'	8' x 18'	8' x 20'	101" x 16'	101" x 18'	101" x 20'
7K Model	H9616TT-070	H9618TT-070	H9620TT-070	H10116TT-070	H10118TT-070	H10120TT-070
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500
GWVR (lb.)	7000	7000	7000	7000	7000	7000
Curb Weight (lb.)	2770	3050	3270	2850	3130	3350
Payload Capacity (lb.)	4230	3950	3730	4150	3870	3650
10K Model	H9616TT-100	H9618TT-100	H9620TT-100	H10116TT-100	H10118TT-100	H10120TT-100
GAWR (lb./axle)	5200	5200	5200	5200	5200	5200
GWVR (lb.)	9900	9900	9900	9900	9900	9900
Curb Weight (lb.)	2950	3250	3470	3050	3300	3550
Payload Capacity (lb.)	6950	6650	6430	6850	6600	6350
Frame Construction	4" Tube Steel	6" Tube Steel	6" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Full Tubular Steel, 16" OC			Full Tubular Steel, 16" OC		
Wall Uprights	Full Tubular Steel, 16" OC			Full Tubular Steel, 16" OC		
Roof Bows	Galvanized Tube Steel, 16" OC			Galvanized Tube Steel, 16" OC		
Exterior Sheeting	.040 Aluminum	.040 Aluminum	.040 Aluminum	.040 Aluminum	.040 Aluminum	.040 Aluminum
Tongue Construction	4" Tube Steel	6" Tube Steel	6" Tube Steel	4" Triple Tube Steel	6" Triple Tube Steel	6" Triple Tube Steel
Coupler	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
Coupler Height	21"	23"	23"	23"	23"	23"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back
Axle Type	Torsion Brake	Torsion Brake	Torsion Brake	Torsion Brake	Torsion Brake	Torsion Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes
Tires: 7K	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels: 7K	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light			(2) 12V, LED Dome Light		
Side Escape Door	Yes	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	74 1/2" x 90"	74 1/2" x 90"	74 1/2" x 90"	74 1/2" x 95"	74 1/2" x 95"	74 1/2" x 95"
Load Capacity (lb.)	4000	4000	4000	4000	4000	4000
Overall Length	20'-7"	22'-7"	24'-7"	20'-7"	22'-7"	24'-7"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height: 7K	8'-8"	8'-8"	8'-8"	8'-8"	8'-8"	8'-8"
10K	8'-9"	8'-9"	8'-9"	8'-9"	8'-9"	8'-9"
Interior Length	16'-9"	18'-9"	20'-9"	16'-9"	18'-9"	20'-9"
Interior Width	15'-10"	17'-10"	19'-10"	15'-10"	17'-10"	19'-10"
Between Wheel Wells	93"	93"	93"	98 1/2"	98 1/2"	98 1/2"
Interior Height	82"	82"	82"	82"	82"	82"
Deck Height: 7K	82"	82"	82"	82"	82"	82"
10K	22"	22"	22"	22"	22"	22"
Deck Box Length	23"	23"	23"	23"	23"	23"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Tube Frame Steel Tube Crossmembers Steel Tube Wall Uprights Galvanized Steel Tube Row Bows Body Fully Undercoated and Vapor Barrier Round Roof with .030 Aluminum Sheeting Custom Fiberglass Nose Cap White on White Black on Color Steel Tube A-Frame Tongue 2 5/16" A-Frame Posi-Lock Coupler 	<ul style="list-style-type: none"> Dual Safety Chains and Hooks 7K Rated Drop Leg Jack .040 Aluminum Exterior Sheeting Standard Color Options: White / Black 24" Aluminum Tread Plate Rock Guard Weather Coated Tongue and Rear Bulkhead 3/8" Engineered Wood Interior Walls - 72" Height Aluminum H-Channel Wall Transitions 3/4" Engineered Wood Flooring 	<ul style="list-style-type: none"> 36" Side Door RV-Style Latch Aluminum Door Hold Back Spring Assist Rear Ramp Door Ramp Transition Flap and Spring Cover Aluminum Teardrop Fenders Torsion Brake Suspension with Easy Lube Hubs Radial Tires on Aluminum Wheels (2) 12V LED Dome Light and Switch, Wall Mounted Full LED, DOT Compliant Lighting (1) Posi-Vent
--	--	--



Specification Page

TOPLINE[®] SERIES CARGO

101" WIDE ENCLOSED TRAILERS

	101" x 16' GN	101" x 18' GN	101" x 20' GN
10K Model	H10116TTGN-100	H10118TTGN-100	H10120TTGN-100
GAWR (lb./axle)	5200	5200	5200
GWVR (lb.)	9900	9900	9900
Curb Weight (lb.)	4700	4900	5100
Payload Capacity (lb.)	5200	5000	4800
14K Model	H10116TTGN-140	H10118TTGN-140	H10120TTGN-140
GAWR (lb./axle)	7000	7000	7000
GWVR (lb.)	14000	14000	14000
Curb Weight (lb.)	4850	5050	5250
Payload Capacity (lb.)	9150	8950	8750
16K Model	H10116TTGN-160	H10118TTGN-160	H10120TTGN-160
GAWR (lb./axle)	8000	8000	8000
GWVR (lb.)	16000	16000	16000
Curb Weight (lb.)	5150	5300	5500
Payload Capacity (lb.)	10850	10700	10500
Frame : 10K	4" Tube Steel	6" Tube Steel	6" Tube Steel
Frame: 14K and 16K	6" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC
Wall Uprights	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC
Roof Bows	Galvanized Tube Steel, 16" OC	Galvanized Tube Steel, 16" OC	Galvanized Tube Steel, 16" OC
Exterior Sheeting	.040 Aluminum	.040 Aluminum	.040 Aluminum
Tongue Construction	6" Tube Steel	6" Tube Steel	6" Tube Steel
Coupler	2-5/16" Adj. Height	2-5/16" Adj. Height	2-5/16" Adj. Height
Coupler Height	35" - 43"	35" - 43"	35" - 43"
Safety Chains	Yes	Yes	Yes
Jack	(2) 12K Rated Drop Leg	(2) 12K Rated Drop Leg	(2) 12K Rated Drop Leg
Axle Type	Torsion Brake	Torsion Brake	Torsion Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes
Tire Size: 10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
14K	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'
16K	ST215/75R17.5 'H'	ST215/75R17.5 'H'	ST215/75R17.5 'H'
Wheels: 10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
14K	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5
16K	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes
Side Door Height x Width	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (HxW)	74 1/2" x 95"	74 1/2" x 95"	74 1/2" x 95"
Load Capacity (lb.)	4000	4000	4000
Overall Length	24'-4"	26'-4"	28'-4"
Overall Width	102"	102"	102"
Overall Height: 10K	8'-10"	9'-0"	9'-0"
14K	8'-11"	9'-1"	9'-1"
16K	9'-0"	9'-2"	9'-2"
Interior Box Length	15'-6"	17'-6"	19'-6"
Interior Width	98 1/2"	98 1/2"	98 1/2"
Between Wheel Wells	82"	82"	82"
Interior Height	83"	83"	83"
Deck Height: 10K	22"	24"	24"
14K	23"	25"	25"
16K	24"	26"	26"