# TANDEM AXLE GRAVITY TILT

*Shown with drive-over fenders

## FEATURES

- Steel Channel Frame and Crossmembers
- 6” Steel Channel Tongue
- Steel Formed Tread Plate Fenders
- Hydraulic Cushion Load Cylinder
- Cylinder Shut-Off Valve & Heavy Duty Hinge Latches
- Adjustable Height Coupler and Dual Safety Chains
- 12K Drop Leg Jack
- Treated, #1 Grade Wood Deck
- Front & Rear Board End Caps
- Drop Spring Brake Axles & EZ Lube Hubs
- Radial Tires on Steel Wheels
- Spare Tire Mount
- Full DOT Compliant, LED Lighting
- Sealed Wiring Harness
- Stake Pockets
- Bulkhead

## OPTIONS

- Adjustable Pintle Ring
- Gooseneck Hitch Upgrade
- Steel Removable Teardrop Fender
- Tongue Mounted Toolbox
- Spare Tire
- Multiple Color Options Available
- ***Contact Your Local Dealer for More Options***

© 2019 Novae Corp. All Rights Reserved.

# TANDEM AXLE GRAVITY TILT

## 14K

| Model Size | 82" x 16'+4' | 82" x 16'+6' | 82" x 18'+4' | 82" x 18'+6' | 82" x 20'+4' |
|---|---|---|---|---|---|
| GAWR (lb/axle) | 7000 | 7000 | 7000 | 7000 | 7000 |
| *Gross Capacity (GVWR) | 14000 | 14000 | 14000 | 14000 | 14000 |
| *Curb Weight (lb) | 3200 | 3310 | 3310 | 3540 | 3540 |
| *Payload Capacity (lb) | 10800 | 10690 | 10690 | 10460 | 10460 |
| Frame Construction | 6" Channel | 6" Channel | 6" Channel | 6" Channel | 6" Channel |
| Crossmembers | 3" Channel 16" OC | 3" Channel 16" OC | 3" Channel 16" OC | 3" Channel 16" OC | 3" Channel 16" OC |
| Tongue Construction | 6" Channel, Wrapped | 6" Channel, Wrapped | 6" Channel, Wrapped | 6" Channel, Wrapped | 6" Channel, Wrapped |
| Tongue Length | 55" | 55" | 55" | 55" | 55" |
| Coupler | 2-5/16" Adj. Height | 2-5/16" Adj. Height | 2-5/16" Adj. Height | 2-5/16" Adj. Height | 2-5/16" Adj. Height |
| Coupler Height | 11"-19" | 11"-19" | 11"-19" | 11"-19" | 11"-19" |
| Safety Chains & Hooks | Yes | Yes | Yes | Yes | Yes |
| Jack | 12K Drop Leg | 12K Drop Leg | 12K Drop Leg | 12K Drop Leg | 12K Drop Leg |
| Axle Type | Drop Spring Brake | Drop Spring Brake | Drop Spring Brake | Drop Spring Brake | Drop Spring Brake |
| Brakes | Yes | Yes | Yes | Yes | Yes |
| Breakaway Kit & Battery | Yes | Yes | Yes | Yes | Yes |
| Tire Size | ST235/75 | ST235/75 | ST235/75 | ST235/75 | ST235/75 |
| Tire Load Range | E | E | E | E | E |
| Tire Ply | Radial | Radial | Radial | Radial | Radial |
| Rim Size | 16" | 16" | 16" | 16" | 16" |
| Bolt Pattern | 8 on 6.5 | 8 on 6.5 | 8 on 6.5 | 8 on 6.5 | 8 on 6.5 |
| Trailer Plug | 7-way | 7-way | 7-way | 7-way | 7-way |
| Exterior Lighting | LED | LED | LED | LED | LED |
| Decking | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine |
| Ramp Style | None | None | None | None | None |
| Overall Length | 24'-5" | 26'-5" | 26'-5" | 28'-5" | 28'-5" |
| Overall Width | 102" | 102" | 102" | 102" | 102" |
| Overall Height | 32" | 32" | 32" | 32" | 32" |
| Deck Height | 19 1/2" | 19 1/2" | 19 1/2" | 19 1/2" | 19 1/2" |
| Deck Length | 20'-0" | 22'-0" | 22'-0" | 24'-0" | 24'-0" |
| Stationary Deck Width | 80" | 80" | 80" | 80" | 80" |
| Tilting Deck Width | 73-3/4" | 73-3/4" | 73-3/4" | 73-3/4" | 73-3/4" |
| Between Fenders Width | 81-3/4" | 81-3/4" | 81-3/4" | 81-3/4" | 81-3/4" |

## 16K

| Model Size | 82" x 16'+4' | 82" x 16'+6' | 82" x 18'+4' | 82" x 18'+6' | 82" x 20'+4' |
|---|---|---|---|---|---|
| GAWR (lb/axle) | 8000 | 8000 | 8000 | 8000 | 8000 |
| *Gross Capacity (GVWR) | 16000 | 16000 | 16000 | 16000 | 16000 |
| *Curb Weight (lb) | 3710 | 3910 | 3910 | 4100 | 4100 |
| *Payload Capacity (lb) | 12290 | 12090 | 12090 | 11900 | 11900 |
| Frame Construction | 8" Channel | 8" Channel | 8" Channel | 8" Channel | 8" Channel |
| Crossmembers | 3" Channel 16" OC | 3" Channel 16" OC | 3" Channel 16" OC | 3" Channel 16" OC | 3" Channel 16" OC |
| Tongue Construction | 6" Channel, Wrapped | 6" Channel, Wrapped | 6" Channel, Wrapped | 6" Channel, Wrapped | 6" Channel, Wrapped |
| Tongue Length | 55" | 55" | 55" | 55" | 55" |
| Coupler | 2-5/16" Adj. Height | 2-5/16" Adj. Height | 2-5/16" Adj. Height | 2-5/16" Adj. Height | 2-5/16" Adj. Height |
| Coupler Height | 11"-19" | 11"-19" | 11"-19" | 11"-19" | 11"-19" |
| Safety Chains & Hooks | Yes | Yes | Yes | Yes | Yes |
| Jack | 12K Drop Leg | 12K Drop Leg | 12K Drop Leg | 12K Drop Leg | 12K Drop Leg |
| Axle Type | Drop Spring Brake | Drop Spring Brake | Drop Spring Brake | Drop Spring Brake | Drop Spring Brake |
| Brakes | Yes | Yes | Yes | Yes | Yes |
| Breakaway Kit & Battery | Yes | Yes | Yes | Yes | Yes |
| Tire Size | 215/75 | 215/75 | 215/75 | 215/75 | 215/75 |
| Tire Load Range | H | H | H | H | H |
| Tire Ply | Radial | Radial | Radial | Radial | Radial |
| Rim Size | 17.5" | 17.5" | 17.5" | 17.5" | 17.5" |
| Bolt Pattern | 8 on 6.5 | 8 on 6.5 | 8 on 6.5 | 8 on 6.5 | 8 on 6.5 |
| Trailer Plug | 7-way | 7-way | 7-way | 7-way | 7-way |
| Exterior Lighting | LED | LED | LED | LED | LED |
| Decking | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine | No. 1 Grade, Pressure Treated Pine |
| Ramp Style | None | None | None | None | None |
| Ramp Height | n/a | n/a | n/a | n/a | n/a |
| Ramp Width | n/a | n/a | n/a | n/a | n/a |
| Ramp Load Capacity (lb/ea) | n/a | n/a | n/a | n/a | n/a |
| Overall Length | 24'-5" | 26'-5" | 26'-5" | 28'-5" | 28'-5" |
| Overall Width | 102" | 102" | 102" | 102" | 102" |
| Overall Height | 34" | 34" | 34" | 34" | 34" |
| Deck Height | 21" | 21" | 21" | 21" | 21" |
| Deck Length | 20'-0" | 22'-0" | 22'-0" | 24'-0" | 24'-0" |
| Stationary Deck Width | 80" | 80" | 80" | 80" | 80" |
| Tilting Deck Width | 73-3/4" | 73-3/4" | 73-3/4" | 73-3/4" | 73-3/4" |
| Between Fenders Width | 81-3/4" | 81-3/4" | 81-3/4" | 81-3/4" | 81-3/4" |

© 2019 Novae Corp. All Rights Reserved.