



TOPLINE SERIES CAR HAULER

ENCLOSED TRAILERS

	101" x 20'	101" x 24'	101" x 28'
10K Model	H10120CRCH-100	H10124CRCH-100	H10128CRCH-100
GAWR (lb./axle)	5200	5200	5200
GWVR (lb.)	9900	9900	9900
Curb Weight (lb.)	3750	4060	4350
Payload Capacity (lb.)	6150	5840	5550
14K Model	H10120CRCH-140	H10124CRCH-140	H10128CRCH-140
GAWR (lb./axle)	7000	7000	7000
GWVR (lb.)	14000	14000	14000
Curb Weight (lb.)	4000	4275	4525
Payload Capacity (lb.)	10000	9725	9475
Frame Construction	6" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Full Tube Steel, 16" OC	Full Tube Steel, 16" OC	Full Tube Steel, 16" OC
Wall Uprights	Full Tube Steel, 16" OC	Full Tube Steel, 16" OC	Full Tube Steel, 16" OC
Roof Bows	Galvanized Tube Steel, 16" OC	Galvanized Tube Steel, 16" OC	Galvanized Tube Steel, 16" OC
Exterior Sheeting	.040 Aluminum	.040 Aluminum	.040 Aluminum
Tongue Construction	6" Tube Steel	6" Tube Steel	6" Tube Steel
Coupler: 10K	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
14K	2-5/16" Adj. Height	2-5/16" Adj. Height	2-5/16" Adj. Height
Coupler Height	21"	21"	21"
Safety Chains	Yes	Yes	Yes
Jack	7K Rated, Set-back	7K Rated, Set-back	7K Rated, Set-back
Axle Type	Torsion Brake	Torsion Brake	Torsion Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes
Tire Size: 10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
14K	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'
Wheels: 10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
14K	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes
Side Door Height x Width	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	76 1/2" x 95"	76 1/2" x 95"	76 1/2" x 95"
Load Capacity (lb.)	4000	4000	4000
Overall Length	24'-7"	28'-7"	32'-7"
Overall Width	102"	102"	102"
Overall Height: 10K	8'-10"	8'-10"	8'-10"
14K	8'-11"	8'-11"	8'-11"
Overall Interior Length	20'-9"	24'-9"	28'-9"
Deck Box Length	19'-10"	23'-10"	27'-10"
Interior Width	98 1/2"	98 1/2"	98 1/2"
Between Wheel Wells	82"	82"	82"
Interior Height	83"	83"	83"
Deck Height: 10K	24"	24"	24"
14K	25"	25"	25"



TOPLINE SERIES GOOSENECK CAR HAULER ENCLOSED TRAILERS

	101" x 20' GN	101" x 24' GN	101" x 28' GN	101" x 32' GN
10K Model	H10120CRCH-100	H10124CRCH-100	H10128CRCH-100	H10132CRCH-100
GAWR (lb./axle)	5200	5200	5200	5200
GWVR (lb.)	9900	9900	9900	9900
Curb Weight (lb.)	4925	5225	5650	6250
Payload Capacity (lb.)	4975	4675	4250	3650
14K Model	H10120CRCH-140	H10124CRCH-140	H10128CRCH-140	H10132CRCH-140
GAWR (lb./axle)	7000	7000	7000	7000
GWVR (lb.)	14000	14000	14000	14000
Curb Weight (lb.)	5100	5400	5870	6470
Payload Capacity (lb.)	8900	8600	8130	7530
16K Model	H10120CRCH-160	H10124CRCH-160	H10128CRCH-160	H10132CRCH-160
GAWR (lb./axle)	8000	8000	8000	8000
GWVR (lb.)	16000	16000	16000	16000
Curb Weight (lb.)	5350	5650	6130	6700
Payload Capacity (lb.)	10650	10350	9870	9300
Frame Construction	6" Tube Steel	6" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC
Wall Uprights	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC	Full Tubular Steel, 16" OC
Roof Bows	Galvanized Tube Steel, 16" OC	Galvanized Tube Steel, 16" OC	Galvanized Tube Steel, 16" OC	Galvanized Tube Steel, 16" OC
Exterior Sheeting	.040 Aluminum	.040 Aluminum	.040 Aluminum	.040 Aluminum
Tongue Construction	6" Tube Steel Gooseneck	6" Tube Steel Gooseneck	6" Tube Steel Gooseneck	6" Tube Steel Gooseneck
Coupler	2-5/16" Adj. Height	2-5/16" Adj. Height	2-5/16" Adj. Height	2-5/16" Adj. Height
Coupler Height	35"-43"	35"-43"	35"-43"	35"-43"
Safety Chains	Yes	Yes	Yes	Yes
Jack	(2) 12K Rated Drop Leg	(2) 12K Rated Drop Leg	(2) 12K Rated Drop Leg	(2) 12K Rated Drop Leg
Axle Type	Torsion Brake	Torsion Brake	Torsion Brake	Torsion Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes
Tire Size: 10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
14K	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'
16K	ST215/75R17.5 'H'	ST215/75R17.5 'H'	ST215/75R17.5 'H'	ST215/75R17.5 'H'
Wheels: 10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
14K	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5
16K	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes	Yes
Side Door Height x Width	68" x 36"	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	76 1/2" x 95"	76 1/2" x 95"	74 1/2" x 95"	74 1/2" x 95"
Load Capacity (lb.)	4000	4000	4000	4000
Overall Length	28'-4"	32'-4"	36'-4"	40'-4"
Overall Width	102"	102"	102"	102"
Overall Height: 10K	9'-1"	9'-1"	9'-1"	9'-1"
14K	9'-2"	9'-2"	9'-2"	9'-2"
16K	9'-3"	9'-3"	9'-3"	9'-3"
Interior Box Length	19'-6"	23'-6"	27'-6"	31'-6"
Interior Neck Length	7'	7'	7'	7'
Interior Width	98 1/2"	98 1/2"	98 1/2"	98 1/2"
Between Wheel Wells	82 1/2"	82 1/2"	82 1/2"	82 1/2"
Interior Height	83"	83"	83"	83"
Deck Height: 10K	24"	24"	24"	24"
14K	25"	25"	25"	25"
16K	26"	26"	26"	26"