

Specification Page

ATV UTILITY **UTILITY TRAILERS**





	82" x 12' (3K)	82" x 14' (3K)	82" x 14' (7K)	82" x 16' (7K)
Model	H8212SHATV-030	H8214SHATV-030	H8214TSHATV-070	H8216TSHATV-070
GAWR (lb./axle)	3500	3500	3500	3500
GVWR (lb.)	2990	2990	7000	7000
Curb Weight (lb.)	1390	1410	1960	2050
Payload Capacity (lb.)	1600	1580	5040	4950
Frame Construction	4"x3" Angle	4"x3" Angle	4"x3" Angle	4"x3" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube	2"x1-1/2" Tube
Tongue Construction	4" Channel	4" Channel	4" Channel	4" Channel
Coupler	2" A-Frame	2" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains	Yes	Yes	Yes	Yes
Jack	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back
Axle Type	Leaf Spring Idler	Leaf Spring Idler	Leaf Spring Brake	Leaf Spring Brake
Brakes	-	-	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	-	-	Yes	Yes
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5			
Trailer Plug	4-Prong	4-Prong	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED
Decking	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
Ramp Style	Spring Assist Gate	Spring Assist Gate	Spring Assist Gate	Spring Assist Gate
Ramp Length x Width	50" x 77"	50" x 77"	50" x 77"	50" x 77"
Load Capacity (lb.)	2500	2500	2500	2500
Overall Length	16'-2"	18'-2"	18'-2"	20'-2"
Overall Width	102"	102"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	12'-0"	14'-0"	14'-0"	16'-0"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

Steel Angle Frame and Crossmembers 2" x 1-1/2" Steel Tube Uprights 2" x 2" Steel Tube Top Rail (2) 2" X 5' Side Ramp Conversions (3,075 lb. Load Rating) 4" Steel Channel Tongue

2K Rated Set-Back Jack with Foot

A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks 2x8 Treated, #1 Grade Wood Decking Welded Front Board Retainer and Rear End Cap 50" Spring Assisted Gate and Grab Handle Steel Tread Plate Fenders

Spring Suspension with Easy Lube Hubs Radial Tires on Black Steel Wheels Full LED, DOT Compliant Lighting Enclosed Sealed Wiring Harness Stake Pockets Spare Tire Mount