



Specification Page

SOLIDE SIDE - SINGLE AXLE

UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
Model	H6008SS-030	H6010SS-030	H6610SS-030	H6612SS-030	H7610SS-030	H7612SS-030	H8212SS-030	H8214SS-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	830	870	910	1030	1030	1150	1170	1250
Payload Capacity (lb.)	2160	2120	2080	1960	1960	1840	1820	1740
Frame Construction	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	None	None	None	None	None	None	None	None
Uprights/Sides	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel	12ga Steel
Tongue Construction	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Set-Back		2K Rated Set-Back		2K Rated Set-Back		2K Rated Set-Back	
Axle Type	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
Ramp Style	Spring Assist Ramp Gate		Spring Assist Ramp Gate		Spring Assist Ramp Gate		Spring Assist Ramp Gate	
Ramp Length x Width	50" x 55"	50" x 55"	50" x 61"	50" x 61"	50" x 71"	50" x 71"	50" x 77"	50" x 77"
Load Capacity (lb.)	2500	2500	2500	2500	2500	2500	2500	2500
Overall Length	12'-2"	14'-2"	14'-2"	16'-2"	14'-2"	16'-2"	16'-2"	18'-2"
Overall Width	80 1/2"	80 1/2"	86 1/2"	86 1/2"	94 1/2"	94 1/2"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	60 1/4"	60 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

<ul style="list-style-type: none"> 12-Gauge Steel Frame Steel Angle Crossmembers 12-Gauge Steel Sides, 15" Tall 4" Steel Channel Tongue A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks 	<ul style="list-style-type: none"> 2K Rated Set-Back Jack with Foot 2x8 Treated, #1 Grade Wood Decking Welded Front Board Retainer and Rear End Cap 50" Spring Assisted Gate and Grab Handle Steel Tread Plate Fenders Spring Suspension with Easy Lube Hubs 	<ul style="list-style-type: none"> Radial Tires on Black Steel Wheels Enclosed Sealed Wiring Harness Full LED, DOT Compliant Lighting D-Rings Tie Downs Spare Tire Mount
--	--	---



SOLIDE SIDE - TANDEM AXLE

UTILITY TRAILERS



	82" x 14' (7K)	82" x 16' (7K)	82" x 18' (7K)	82" x 20' (7K)
Model	H8214TSS-070	H8216TSS-070	H8218TSS-070	H8220TSS-070
GAWR (lb./axle)	3500	3500	3500	3500
GVWR (lb.)	7000	7000	7000	7000
Curb Weight (lb.)	1610	1790	1890	1970
Payload Capacity (lb.)	5390	5210	5110	5030
Frame Construction	12ga Steel	12ga Steel	12ga Steel	12ga Steel
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	None	None	None	None
Uprights/Sides	12ga Steel	12ga Steel	12ga Steel	12ga Steel
Tongue Construction	4" Channel	4" Channel	4" Channel	4" Channel
Coupler	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains	Yes	Yes	Yes	Yes
Jack	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED
Decking	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
Ramp Style	Spring Assist Ramp Gate	Spring Assist Ramp Gate	Spring Assist Ramp Gate	Spring Assist Ramp Gate
Ramp Length x Width	50" x 77"	50" x 77"	50" x 77"	50" x 77"
Load Capacity (lb.)	2500	2500	2500	2500
Overall Length	18'-2"	20'-2"	22'-2"	24'-2"
Overall Width	102"	102"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	14'-0"	16'-0"	18'-0"	20'-0"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

12-Gauge Steel Frame
Steel Angle Crossmembers
12-Gauge Steel Sides, 15" Tall
4" Steel Channel Tongue
A-Frame Posi-Lock Coupler
Dual Safety Chains and Hooks

2K Rated Set-Back Jack with Foot
2x8 Treated, #1 Grade Wood Decking
Welded Front Board Retainer and Rear End Cap
50" Spring Assisted Gate and Grab Handle
Steel Tread Plate Fenders
Spring Suspension with Easy Lube Hubs

Radial Tires on Black Steel Wheels
Enclosed Sealed Wiring Harness
Full LED, DOT Compliant Lighting
D-Rings Tie Downs
Spare Tire Mount