



Specification Page

WOOD SIDE - SINGLE AXLE

UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
Model	H6008WS-030	H6101WS-030	H6610WS-030	H6612WS-030	H7610WS-030	H7612WS-030	H8212WS-030	H8214WS-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	945	1070	1090	1200	1140	1250	1290	1400
Payload Capacity (lb.)	2045	1920	1900	1790	1850	1740	1700	1590
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1-1/2" Tube 3 Board Treated Pine		2"x1-1/2" Tube 3 Board Treated Pine		2"x1-1/2" Tube 3 Board Treated Pine		2"x1-1/2" Tube 3 Board Treated Pine	
Tongue Construction	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel	4" Channel
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Set-Back		2K Rated Set-Back		2K Rated Set-Back		2K Rated Set-Back	
Axle Type	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
Ramp Style	Spring Assist Ramp Gate		Spring Assist Ramp Gate		Spring Assist Ramp Gate		Spring Assist Ramp Gate	
Ramp Length x Width	50" x 55"	50" x 55"	50" x 61"	50" x 61"	50" x 71"	50" x 71"	50" x 77"	50" x 77"
Load Capacity (lb.)	2500	2500	2500	2500	2500	2500	2500	2500
Overall Length	12'-2"	14'-2"	14'-2"	16'-2"	14'-2"	16'-2"	16'-2"	18'-2"
Overall Width	80 1/2"	80 1/2"	86 1/2"	86 1/2"	94 1/2"	94 1/2"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	58 1/2"	58 1/2"	64 1/2"	64 1/2"	74 1/2"	74 1/2"	80 1/2"	80 1/2"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Angle Frame and Crossmembers 2" x 2" Steel Tube Top Rail 2" x 1-1/2" Steel Tube Uprights 3 Treated Boards High Sides 4" Steel Channel Tongue A-Frame Posi-Lock Coupler 	<ul style="list-style-type: none"> Dual Safety Chains and Hooks 2K Rated Set-Back Jack with Foot 2x8 Treated, #1 Grade Wood Decking Welded Front Board Retainer and Rear End Cap 50" Spring Assisted Gate and Grab Handle Steel Tread Plate Fenders 	<ul style="list-style-type: none"> Spring Suspension with Easy Lube Hubs Radial Tires on Black Steel Wheels Full LED, DOT Compliant Lighting Enclosed Sealed Wiring Harness D-Ring Tie Downs, Floor and Side Mount Spare Tire Mount
---	---	---